

75 Ohm 1.0/2.3 Jack Bulkhead Mount Push-On Connector Solder Attachment End Launch PCB



RF Connectors Technical Data Sheet

ET09768

Configuration

- Push-On 1.0/2.3 Jack Connector
- 75 Ohms
- Straight Body Geometry

Features

- Push-On connection
- Secure locking mechanism

- End Launch Interface Type
- Solder Attachment
- Bulkhead
- Performance to 3 GHz
- 500 Mating cycles

Applications

Data Communications

Video Processors

Switching Equipment

Description

Ebeestock's 75 Ohm DIN 1.0/2.3 connectors allow for a secure locking push-pull connection. These 1.0/2.3 connectors have an impedance of 75 Ohms and operate to 3 GHz, making these RF connectors an excellent choice for many data communications and audio/video applications. The small size of these 75 ohm 1.0/2.3 DIN connectors allows for a dense connector-to-connector footprint, saving valuable space in panels and other applications requiring a high number of interconnects. The durable positive locking connectors have a mating life of up to 500 connections.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		3	GHz
VSWR			1.15:1	

Mechanical Specifications

Size

 Length
 0.647 in [16.43 mm]

 Width/Dia.
 0.287 in [7.29 mm]

 Weight
 0.006 lbs [2.72 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 75 Ohm 1.0/2.3 Jack Bulkhead Mount Push-On Connector Solder Attachment End Launch PCB ET09768

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



75 Ohm 1.0/2.3 Jack Bulkhead Mount Push-On Connector Solder Attachment End Launch PCB



RF Connectors Technical Data Sheet

ET09768

Material Specifications

Description	Material	Plating	
Contact	Beryllium Copper	Gold	
Insulation	PTFE		
Outer Conductor	Brass	Gold	
Body	Brass	Gold	
Washer	Brass	Gold	

Environmental Specifications

Temperature

Operating Range

-65 to 165 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

75 Ohm 1.0/2.3 Jack Bulkhead Mount Push-On Connector Solder Attachment End Launch PCB from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 75 Ohm 1.0/2.3 Jack Bulkhead Mount Push-On Connector Solder Attachment End Launch PCB ET09768

URL: https://www.ebeestock.com/75-ohm-1-0-2-3-jack-bulkhead-mount-push-on-connector-solder-atta chment-end-launch-pcb-0009768

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. <a href="Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

ET09768 CAD Drawing
75 Ohm 1.0/2.3 Jack Bulkhead Mount Push-On Connector Solder Attachment End Launch PCB

