BNC Male Right Angle Connector Crimp/Solder Attachment for RG174, RG316, RG188, .100 inch, PE-B100, PE-C100, LMR-100 REVISIONS DESCRIPTION DATE APPROVED .57 REVISE STRIPPING DIMENSIONS 11/4/21 **SELLIS** 14.5 REF. 1.06±.02 Ø.146 27.0±0.5 3.70 Ø.024 .374 REF. 0.60 9.50 0 CONTACT .295 7.50 .248 .276 6.30 7.00 1.44±.02 36.6±0.5 INSULATION **METAL SPACER** B .690 Ø.118^{+.004}_{-.002} [17.53] Ø.213 .587±.012 3.00^{+0.10} -0.05 [5.40] 14.90±0.30 .280 7.11 .140 $\emptyset.173$ 3.56 4.40 **FERRULE** STRIPPING DIMENSIONS THIRD-ANGLE PROJECTION UNLESS OTHERWISE SPECIFIED ebeestock LEADING DIMENSIONS ARE INCHES DIMENSIONS IN [] ARE MILLIMETERS NOTES: **TOLERANCES** CABLE ATTACHMENT: THE INFORMATION AND DESIGN IN THIS DOCUMENT $.X = \pm .2$ [5.08] **FRACTIONS** 8TH FLOOR, BUILDING 1, OUTER: CRIMP. $.XX = \pm .02$ [.51] ± 1/32 IS THE PROPERTY OF EBEESTOCK. ALL RIGHTS YONGFU SCIENCE AND TECHNOLOGY $.XXX = \pm .005$ [.13] ANGLES ± 1° INNER: SOLDER/CRIMP. CABLE LENGTH (L) TOLERANCES: CENTER INDUSTRIAL PARK, NANZHA DISTRICT 2. CRIMP SIZE REQUIRED: 5.HUMEN.523900.DONGGUAN, GUANGDONG, CHINA SHEET OF L ≤ 12 [305] = +1 [25] / -0 12 [305] < L ≤ 60 [1524] = +2 [51] / -0 FERRULE: .178 [4.52] HEX. CRIMP TOOL WEBSITE: www.ebeestock.com 60 [1524] < L ≤ 120 [3048] = +4 [102] / -0 SCALE EMAIL: sales@ebeestock.com CONTACT: .068 [1.73] HEX. CRIMP TOOL. N/A 120 [3048] < L ≤ 300 [7620] = +6 [152] / -0

300 [7620] < L = +5%L / -0

ALL DIMENSIONS SHOWN

ARE FOR REFERENCE ONLY.

SIZE CAGE CODE DRAWN BY

KDANG

53919

REV

ET10374

В

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE

WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.