

N Male Connector Crimp/Solder Attachment for ET38328, ET3837

7, ET38377-DB, 0.600 inch



# RF Connectors Technical Data Sheet

ET10914

### Configuration

- N Male Connector
- 50 Ohms
- Straight Body Geometry

- Connector Interface Types: ET38328, ET38377, LMR-600-DB, .600 inch
- 18 mm Hex

#### Features

Max. Operating Frequency 11 GHz

Gold Plated Brass Contact

### Applications

General Purpose Test

Custom Cable Assemblies

#### Description

Ebeestock's ET10914 type N male connector with crimp/solder attachment for ET38328, ET38377, ET38371 and .600 inch is part of our full line of RF components available for same-day shipping. Our type N male connector operates up to a maximum frequency of 11 GHz.

Our type N male connector ET10914 datasheet specifications and drawing with dimensions are shown below in this PDF. Ebeestock's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Ebeestock has the right connector for the job. Ebeestock can also expertly build your custom cable assemblies for you and ship same-day.

#### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		11	GHz

#### Mechanical Specifications

#### Size

 Length
 2.03 in [51.56 mm]

 Width/Dia.
 0.95 in [24.13 mm]

 Weight
 0.161 lbs [73.03 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Male Connector Crimp/Solder Attachment for ET38328, ET38377, ET38371, 0.600 inch ET10914

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



N Male Connector Crimp/Solder Attachment for ET38328, ET3837

7, ET38377-DB, 0.600 inch



# RF Connectors Technical Data Sheet

ET10914

#### **Material Specifications**

Description	Material	Plating
Contact	Brass	Gold
Insulation	PTFE	
Body	Brass	Tri-Metal
Coupling Nut	Brass	Tri-Metal

## Environmental Specifications

Temperature

Operating Range

-65 to +165 deg C

Compliance Certifications (see product page for current document)

#### Plotted and Other Data

Notes:

N Male Connector Crimp/Solder Attachment for ET38328, ET38377, ET38371, 0.600 inch from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Male Connector Crimp/Solder Attachment for ET38328, ET38377, ET38371, 0.600 inch ET10914

**URL:** https://www.ebeestock.com/n-male-connector-crimp-solder-attachment-for-pe-c600-lmr-600-lmr -600-db-0-600-inch-0010914

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.

# ET10914 CAD Drawing

N Male Connector Crimp/Solder Attachment for ET-C600, ET38377, ET38371, 0.600 inch

