

N Male Right Angle Connector Crimp/Solder Attachment for ET3 8362, ET38397, .240 inch, ET38379, ET38379-DB, ET38379-UF, B7808A



RF Connectors Technical Data Sheet

ET10916

Configuration

- N Male Connector
- 50 Ohms
- Right Angle Body Geometry

- ET38362, ET38397, 0.240 inch, ET38379, ET38374, ET38373, B7808A Interface Type
- Crimp/Solder Attachment

Features

• Max. Operating Frequency 11 GHz

Gold Plated Brass Contact

Applications

General Purpose Test

Custom Cable Assemblies

Description

Ebeestock's ET10916 type N male right angle connector with crimp/solder attachment for ET38362, ET38397, 0.240 inch, ET38379, ET38374, ET38373 and B7808A is part of our full line of RF components available for same-day shipping. Our type N male connector operates up to a maximum frequency of 11 GHz. Its right angle body geometry allows for easier connections in tight spaces.

Our type N male right angle connector ET10916 datasheet specifications and drawing with dimensions are shown below in this PDF. Ebeestock's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Ebeestock has the right connector for the job. Ebeestock can also expertly build your custom cable assemblies for you and ship same-day.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		11	GHz

Mechanical Specifications

Length1.21 in [30.73 mm]Width/Dia.0.83 in [21.08 mm]Height1.117 in [28.37 mm]Weight0.097 lbs [44 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Male Right Angle Connector Crimp/Solder Attachment for ET38362, ET38397, 0.240 inch, ET38379, ET38374, ET38373, B7808A ET10916

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



N Male Right Angle Connector Crimp/Solder Attachment for ET3 8362, ET38397, .240 inch, ET38379, ET38379-DB, ET38379-UF, B7808A



RF Connectors Technical Data Sheet

ET10916

Material Specifications

Description	Material	Plating
Contact	Brass	Gold
Insulation	PTFE	
Body	Brass	Tri-Metal

Environmental Specifications

Temperature

Operating Range

-65 to +165 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

N Male Right Angle Connector Crimp/Solder Attachment for ET38362, ET38397, 0.240 inch, ET38379, ET38374, ET38379-UF, B7808A from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Male Right Angle Connector Crimp/Solder Attachment for ET38362, ET38397, 0.240 inch, LMR- 240, ET38374, ET38373, B7808A ET10916

URL: https://www.ebeestock.com/n-male-right-angle-connector-crimp-solder-attachment-for-pe-c240 -rg8x-240-inch-lmr-240-lmr-240-db-lmr-240-uf-b7808a-0010916

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



