

N Female Connector Crimp/Solder Attachment for ET38362, ET38 397, 0.240 inch, ET38379, ET38379-DB, ET38379-UF, B7808A



# RF Connectors Technical Data Sheet

ET10924

## Configuration

- N Female Connector
- 50 Ohms
- Straight Body Geometry

Connector Interface Types: ET38362, ET38397, .240 inch, ET38379, ET38374, ET38373, B7808A

### Features

• Max. Operating Frequency 11 GHz

Gold Plated Beryllium Copper Contact

## Applications

General Purpose Test

Custom Cable Assemblies

#### Description

Ebeestock's ET10924 type N female connector with crimp/solder attachment for ET38362, ET38397, .240 inch, ET38379, ET38374, ET38373 and B7808A is part of our full line of RF components available for same-day shipping. Our type N female connector operates up to a maximum frequency of 11 GHz.

Our type N female connector ET10924 datasheet specifications and drawing with dimensions are shown below in this PDF. Ebeestock's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Ebeestock has the right connector for the job. Ebeestock can also expertly build your custom cable assemblies for you and ship same-day.

### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		11	GHz
Operating Voltage (AC)			830	Vrms
Dielectric Withstanding Voltage (AC)			2,500	Vrms

## Mechanical Specifications

	70
-	
<b>3</b>	

 Length
 1.45 in [36.83 mm]

 Width/Dia.
 0.67 in [17.02 mm]

 Height
 0.67 in [17.02 mm]

 Weight
 0.069 lbs [31.3 g]

 Mating Cycles
 500 Cycles

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Female Connector Crimp/Solder Attachment for ET38362, ET38397, 0.240 inch, ET38379, ET38374, ET38373, B7808A ET10924

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



N Female Connector Crimp/Solder Attachment for ET38362, ET38 397, 0.240 inch, ET38379, ET38379-DB, ET38379-UF, B7808A



# RF Connectors Technical Data Sheet

ET10924

#### Material Specifications

Description	Material	Plating	
Contact	Beryllium Copper	Gold	
Insulation	PTFE		
Body	Brass	Tri-Metal	

# **Environmental Specifications**

Temperature

Operating Range

-65 to +165 deg C

Compliance Certifications (see product page for current document)

#### Plotted and Other Data

Notes:

N Female Connector Crimp/Solder Attachment for ET38362, ET38397, 0.240 inch, ET38379, ET38374, ET38373, B7808A from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Female Connector Crimp/Solder Attachment for ET38362, ET38397, 0.240 inch, ET38379, LMR- 240-DB, ET38373, B7808A ET10924

**URL:** https://www.ebeestock.com/n-female-connector-crimp-solder-attachment-for-pe-c240-rg8x-0-24 0-inch-lmr-240-lmr-240-db-lmr-240-uf-b7808a-0010924

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. <a href="Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.</a>

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.

