

N Male Precision Connector Threaded Attachment for VNA Test Cable



RF Connectors Technical Data Sheet

ET10993

Configuration

- N Male Connector
- MIL-STD-348A
- 50 Ohms

Straight Body Geometry

- Connector Interface Types: VNA Test Cable
- Precision Design

Features

- Max. Operating Frequency 18 GHz
- Excellent VSWR of 1.2:1

- Gold Plated Beryllium Copper Contact
- 50 [1.27] μin. [μm] minimum contact plating

Applications

- General Purpose Test
- Precision Test & Measurement
- Custom Cable Assemblies

Description

Ebeestock's ET10993 type N male connector with threaded attachment for VNA test cable is part of our full line of RF components available for same-day shipping. Our type N male connector operates up to a maximum frequency of 18 GHz and offers excellent VSWR of 1.2:1.

Our type N male connector ET10993 datasheet specifications and drawing with dimensions are shown below in this PDF. Ebeestock's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Ebeestock has the right connector for the job. Ebeestock can also expertly build your custom cable assemblies for you and ship same-day.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		18	GHz
VSWR			1.2:1	
Return Loss			21	dB
Insertion Loss			0.21	dB
Operating Voltage (AC)			335	Vrms
Dielectric Withstanding Voltage (AC)			1,000	Vrms
Inner Conductor DC Resistance			1	mOhms
Outer Conductor DC Resistance			1	mOhms
RF Leakage	90			dB

Mechanical Specifications

Size

Length
Width/Dia.

1.3 in [33.02 mm] 0.787 in [19.99 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Male Precision Connector Threaded Attachment for VNA Test Cable ET10993

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



N Male Precision Connector Threaded Attachment for VNA Test Cable



RF Connectors Technical Data Sheet

ET10993

Weight 0.082 lbs [37.19 g]
Mating Cycles 500 Cycles

Material Specifications

Description	Material	Plating	
Contact	Beryllium Copper	Gold 50 [1.27] µin. [µm] minimum	
Insulation	PPE		
Body	Passivated Stainless Steel		
Coupling Nut	Passivated Stainless Steel		

Mechanical Specification Notes: Recommended torque: 2 Nm

Environmental Specifications

Temperature

Operating Range -40 to +85 deg C

Humidity MIL-STD-202, Method 106

Shock

MIL-STD-202, Method 213, Condition I

Vibration

MIL-STD-202, Method 204, Condition D

Salt Spray

MIL-STD-202, Method 101, Condition B

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Male Precision Connector Threaded Attachment for VNA Test Cable ET10993



N Male Precision Connector Threaded Attachment for VNA Test Cable



RF Connectors Technical Data Sheet

ET10993

N Male Precision Connector Threaded Attachment for VNA Test Cable from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Male Precision Connector Threaded Attachment for VNA Test Cable ET10993

URL: https://www.ebeestock.com/n-male-precision-connector-threaded-attachment-for-vna-test-cable-0010993

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

