

QMA Male Right Angle Connector Crimp/Solder Attachment for E T-ET-RG174, ET-RG316, ET-RG188



RF Connectors Technical Data Sheet

ET11060

Configuration

- QMA Male Connector
- 50 Ohms
- Right Angle Body Geometry

- ET-RG174, ET-RG316, ET-RG188 Interface Type
- Crimp/Solder Attachment

Features

- Max. Operating Frequency 6 GHz
- Good VSWR of 1.35:1

Gold Plated Brass Contact

Applications

General Purpose Test

Custom Cable Assemblies

Description

Ebeestock's ET11060 QMA male right angle connector with crimp/solder attachment for ET-RG174, ET-RG316 and ET-RG188 is part of our full line of RF components available for same-day shipping. Our QMA male connector operates up to a maximum frequency of 6 GHz and offers good VSWR of 1.35:1. Its right angle body geometry allows for easier connections in tight spaces.

Our QMA male right angle connector ET11060 datasheet specifications and drawing with dimensions are shown below in this PDF. Ebeestock's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Ebeestock has the right connector for the job. Ebeestock can also expertly build your custom cable assemblies for you and ship same-day.

Electrical Specifications

Minimum	Typical	Maximum	Units
DC		6	GHz
		1.35:1	
		0.12	dB
		250	Vrms
		750	Vrms
5,000			MOhms
74			dB
	DC 5,000	DC 5,000	DC 6 1.35:1 0.12 250 750 5,000

Mechanical Specifications

Size

 Length
 0.77 in [19.56 mm]

 Width/Dia.
 0.413 in [10.49 mm]

 Height
 0.634 in [16.1 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: QMA Male Right Angle Connector Crimp/Solder Attachment for ET-RG174, ET-RG316, ET-RG188 ET11060

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



QMA Male Right Angle Connector Crimp/Solder Attachment for E T-ET-RG174, ET-RG316, ET-RG188



RF Connectors Technical Data Sheet

ET11060

Weight 0.076 lbs [34.47 g]
Mating Cycles 100 Cycles

Material Specifications

Brass	Gold
PTFE	
Brass	Tri-Metal
Brass	Nickel
	Brass

Environmental Specifications

Temperature

Operating Range

-40 to +105 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

QMA Male Right Angle Connector Crimp/Solder Attachment for ET-RG174, ET-RG316, ET-RG188 from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: QMA Male Right Angle Connector Crimp/Solder Attachment for ET-RG174, ET-RG316, ET-


URL: https://www.ebeestock.com/qma-male-right-angle-connector-crimp-solder-attachment-for-rg174 -rg316-rg188-0011060

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. <a href="Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.

ET11060 CAD Drawing

QMA Male Right Angle Connector Crimp/Solder Attachment for ET-RG174, ET-RG316, ET-RG188



ET11060 REV 1.0