

SMA Male Connector Crimp/Non-Solder Contact Attachment for E T38379, ET38362



RF Connectors Technical Data Sheet



Times Microwave Systems Connector Specification

- Configuration
 - SMA Male Connector
 - MIL-STD-348
 - 50 Ohms

- Straight Body Geometry
- Connector Interface Types: ET38379, ET38362
- 5/16 Inch Hex

Features

- Max. Operating Frequency 6 GHz
- Good VSWR of 1.3:1

- Gold Plated Beryllium Copper Contact
- Contact plating according to ASTM B488

Applications

General Purpose Test

Custom Cable Assemblies

Description

Ebeestock's ET11103 SMA male connector with crimp/non-solder contact attachment for ET38379 and ET38362 is part of our full line of RF components available for same-day shipping. Our SMA male connector operates up to a maximum frequency of 6 GHz and offers good VSWR of 1.3:1.

Our SMA male connector ET11103 datasheet specifications and drawing with dimensions are shown below in this PDF. Ebeestock's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Ebeestock has the right connector for the job. Ebeestock can also expertly build your custom cable assemblies for you and ship same-day.

Electrical Specifications

Minimum	Typical	Maximum	Units
DC		6	GHz
		1.3:1	
		0.25	dB
		1,000	Vrms
10,000			MOhms
	DC	DC	DC 6 1.3:1 0.25 1,000

Mechanical Specifications

Size

 Length
 1.17 in [29.72 mm]

 Width/Dia.
 0.375 in [9.53 mm]

 Weight
 0.02 lbs [9.07 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male Connector Crimp/Non-Solder Contact Attachment for ET38379, ET38362 EZ-240-SM-X

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.

Webstie:www.ebeestock.com Email:sales@ebeestock.com



SMA Male Connector Crimp/Non-Solder Contact Attachment for E T38379, ET38362



RF Connectors Technical Data Sheet



Material Specifications

Description	Material Material Control of the Con	Plating
Contact	Beryllium Copper	Gold ASTM B488
Insulation	PTFE	
Outer Conductor	Brass	Tri-Metal
Body	Brass	Tri-Metal
Coupling Nut	Brass	Tri-Metal

Environmental Specifications

Temperature

Operating Range -40 to +125 deg C

MIL-STD-202G, Meth. 213, Cond I Shock MIL-STD-202G, Meth. 204, Cond B Vibration MIL-STD-202G, Meth. 107, Cond B Thermal Shock

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

SMA Male Connector Crimp/Non-Solder Contact Attachment for ET38379, ET38362 from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male Connector Crimp/Non-Solder Contact Attachment for ET38379, ET38362 EZ-240-SM-X

URL: https://www.ebeestock.com/sma-male-connector-crimp-non-solder-contact-attachment-for-lmr-2 40-pe-c240-0011103

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.

TIMES MICROWAVE SYSTEMS EZ-240-SM-X CAD Drawing SMA Male Connector Crimp/Non-Solder Contact Attachment for LMR-240, PE-C240

