


SMA Female Connector Solder Attachment .031 inch End Launch PCB



RF Connectors Technical Data Sheet

ET11236

Configuration

- SMA Female Connector
- MIL-STD-348A
- 50 Ohms

Features

- Max. Operating Frequency 18 GHz
- Excellent VSWR of 1.23:1

- Straight Body Geometry
- .031 inch End Launch Interface Type
- Solder Attachment
- Gold Plated Beryllium Copper Contact
- 50 µin minimum contact plating

Applications

General Purpose Test

PCB Applications

Description

Ebeestock's ET11236 SMA female connector with solder attachment for .031 inch end launch PCB is part of our full line of RF components available for same-day shipping. Our SMA female connector operates up to a maximum frequency of 18 GHz and offers excellent VSWR of 1.23:1.

Our SMA female connector ET11236 datasheet specifications and drawing with dimensions are shown below in this PDF. Ebeestock's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Ebeestock has the right connector for the job. Ebeestock can also expertly build your custom cable assemblies for you and ship same-day.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		18	GHz
VSWR			1.23:1	
Operating Voltage (AC)			500	Vrms
Dielectric Withstanding Voltage (AC)			1,000	Vrms

Mechanical Specifications

Size

 Length
 0.562 in [14.27 mm]

 Width/Dia.
 0.375 in [9.53 mm]

 Height
 0.312 in [7.92 mm]


 Weight
 0.009 lbs [4.08 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female Connector Solder Attachment .031 inch End Launch PCB ET11236

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



SMA Female Connector Solder Attachment .031 inch End Launch PCB



RF Connectors Technical Data Sheet

ET11236

Material Specifications

Description	Material	Plating
Contact	Beryllium Copper	Gold 50 µin minimum
Insulation	PTFE	
Body	Brass	Gold 3 µin minimum

Environmental Specifications

Temperature

Operating Range

-65 to +165 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

SMA Female Connector Solder Attachment .031 inch End Launch PCB from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female Connector Solder Attachment .031 inch End Launch PCB ET11236

URL: https://www.ebeestock.com/sma-female-connector-solder-attachment-031-inch-end-launch-pcb-0 011236

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

ET11236 CAD Drawing

SMA Female Connector Solder Attachment .031 inch End Launch PCB

