

SMA Female Right Angle Connector Solder Attachment 2 Hole Fl ange Mount Pin Terminal, .481 inch Hole Spacing, -45 Degree Flange Direction



# RF Connectors Technical Data Sheet

ET11252

### Configuration

- SMA Female Connector
- MIL-STD-348
- 50 Ohms
- Right Angle Body Geometry

- Pin Interface Type
- Solder Attachment
- 2 Hole Flange

### Features

- Max. Operating Frequency 18 GHz
- Good VSWR of 1.3:1

- Gold Plated Beryllium Copper Contact
- Contact plating according to MIL-G-45204

# Applications

General Purpose Test

Rack and Panel Mount Applications

### Description

Ebeestock's ET11252 SMA female right angle 2 hole flange mount connector with solder attachment pin terminal (.481 inch hole spacing) is part of our full line of RF components available for same-day shipping. Our SMA female connector operates up to a maximum frequency of 18 GHz and offers good VSWR of 1.3:1. Its right angle body geometry allows for easier connections in tight spaces. This SMA 2 hole flange connector allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

Our SMA female right angle 2 hole flange connector ET11252 datasheet specifications and drawing with dimensions are shown below in this PDF. Ebeestock's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Ebeestock has the right connector for the job. Ebeestock can also expertly build your custom cable assemblies for you and ship same-day.

### Electrical Specifications

Minimum	Typical	Maximum	Units
DC		18	GHz
		1.3:1	
		500	Vrms
		1,500	Vrms
5,000			MOhms
	DC	DC	DC 18 1.3:1 500 1,500

#### Mechanical Specifications

Size

Length
Width/Dia.

1.205 in [30.61 mm]
0.625 in [15.88 mm]
Height
0.598 in [15.19 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female Right Angle Connector Solder Attachment 2 Hole Flange Mount Pin Terminal, .481 inch Hole Spacing, -45 Degree Flange Direction ET11252

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.

Webstie:www.ebeestock.com Email:sales@ebeestock.com



SMA Female Right Angle Connector Solder Attachment 2 Hole Fl ange Mount Pin Terminal, .481 inch Hole Spacing, -45 Degree Flange Direction



### RF Connectors Technical Data Sheet

ET11252

Weight 0.014 lbs [6.35 g]

### Material Specifications

Description	Material	Plating
Contact	Beryllium Copper	Gold MIL-G-45204
Insulation	PTFE	
Body	Brass	Gold MIL-G-45204

# **Environmental Specifications**

Temperature

Operating Range -65 to +165 deg C

Compliance Certifications (see product page for current document)

### Plotted and Other Data

Notes:

SMA Female Right Angle Connector Solder Attachment 2 Hole Flange Mount Pin Terminal, .481 inch Hole Spacing, -45 Degree Flange Direction from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female Right Angle Connector Solder Attachment 2 Hole Flange Mount Pin Terminal, .481 inch Hole Spacing, -45 Degree Flange Direction ET11252

**URL:** https://www.ebeestock.com/sma-female-right-angle-connector-solder-attachment-2-hole-flange -mount-pin-terminal-481-inch-hole-spacing-45-degree-flange-direction-0011252

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. <a href="Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.</a>

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.

