

SMA Female Connector Compression Attachment 2 Hole Flange Mount Stub Terminal, .481 inch Hole Spacing



RF Connectors Technical Data Sheet

ET11260

Configuration

- SMA Female Connector
- 50 Ohms
- Straight Body Geometry

- Stub Interface Type
- Compression Attachment
- 2 Hole Flange

Features

- Max. Operating Frequency 27 GHz
- Excellent VSWR of 1.2:1

- Gold over Nickel Plated Beryllium Copper Contact
- Contact plating according to MIL-G-45204

Applications

General Purpose Test

Rack and Panel Mount Applications

Description

Ebeestock's ET11260 SMA female 2 hole flange mount connector with compression attachment stub terminal (.481 inch hole spacing) is part of our full line of RF components available for same-day shipping. Our SMA female connector operates up to a maximum frequency of 27 GHz and offers excellent VSWR of 1.2:1. This SMA 2 hole flange connector allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

Our SMA female 2 hole flange connector ET11260 datasheet specifications and drawing with dimensions are shown below in this PDF. Ebeestock's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Ebeestock has the right connector for the job. Ebeestock can also expertly build your custom cable assemblies for you and ship same-day.

Electrical Specifications

| Description | Minimum | Typical | Maximum | Units |
|-----------------|---------|---------|---------|-------|
| Frequency Range | DC | | 27 | GHz |
| VSWR | | | 1.2:1 | |
| Insertion Loss | | | 0.26 | dB |
| | | | | |

Electrical Specification Notes: Insertion loss: 0.05 x sqrt(fGHz) dB.

Mechanical Specifications

| _ | | | |
|---|---|---|---|
| C | Н | 7 | |
| | | Z | C |

 Length
 0.562 in [14.27 mm]

 Width/Dia.
 0.223 in [5.66 mm]

 Height
 0.625 in [15.88 mm]

 Weight
 0.005 lbs [2.27 g]

 Mating Cycles
 500 Cycles

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female Connector Compression Attachment 2 Hole Flange Mount Stub Terminal, .481 inch Hole Spacing ET11260

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.

Webstie:www.ebeestock.com Email:sales@ebeestock.com



SMA Female Connector Compression Attachment 2 Hole Flange Mount Stub Terminal, .481 inch Hole Spacing



RF Connectors Technical Data Sheet

ET11260

Material Specifications

| Description | Material | Plating |
|-------------|------------------|---------------------------------|
| Contact | Beryllium Copper | Gold over Nickel MIL-G-45204 |
| Insulation | PTFE | |
| Body | Stainless Steel | Gold MIL-G-45204 |

Environmental Specifications

Temperature

Operating Range Vibration Salt Spray

-55 to +100 deg C MIL-STD-202, Method 204, Condition D (20 G's) MIL-STD-202, Method 101, Condition B, 5% salt solution

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

SMA Female Connector Compression Attachment 2 Hole Flange Mount Stub Terminal, .481 inch Hole Spacing from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female Connector Compression Attachment 2 Hole Flange Mount Stub Terminal, .481 inch Hole Spacing ET11260

URL: https://www.ebeestock.com/sma-female-connector-compression-attachment-2-hole-flange-mount-stub-terminal-481-inch-hole-spacing-0011260

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.

ET11260 CAD Drawing

SMA Female Connector Compression Attachment 2 Hole Flange Mount Stub Terminal, .481 inch Hole Spacing

