

SMA Female Connector Solder Attachment Thru Hole PCB, .200 i nch x .067 inch Hole Spacing



# RF Connectors Technical Data Sheet

ET11262

# Configuration

- SMA Female Connector
- 50 Ohms
- Straight Body Geometry

- Thru Hole Interface Type
- Solder Attachment

### Features

- Max. Operating Frequency 27 GHz
- Excellent VSWR of 1.2:1

- Gold over Nickel Plated Beryllium Copper Contact
- Contact plating according to MIL-G-45204

# Applications

General Purpose Test

PCB Applications

### Description

Ebeestock's ET11262 SMA female connector with solder attachment for thru hole PCB (.200 inch x .067 inch hole spacing) is part of our full line of RF components available for same-day shipping. Our SMA female connector operates up to a maximum frequency of 27 GHz and offers excellent VSWR of 1.2:1.

Our SMA female connector ET11262 datasheet specifications and drawing with dimensions are shown below in this PDF. Ebeestock's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Ebeestock has the right connector for the job. Ebeestock can also expertly build your custom cable assemblies for you and ship same-day.

#### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		27	GHz
VSWR			1.2:1	
Insertion Loss			0.26	dB

Electrical Specification Notes: Insertion loss: 0.05 x sqrt(fGHz) dB.

### Mechanical Specifications

Size	
Length	0.53 in [13.46 mm
Width/Dia.	0.25 in [6.35 mm]
Height	0.25 in [6.35 mm]
Weight	0.005 lbs [2.27 g]
Mating Cycles	500 Cycles

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female Connector Solder Attachment Thru Hole PCB, .200 inch x .067 inch Hole Spacing ET11262



SMA Female Connector Solder Attachment Thru Hole PCB, .200 i nch x .067 inch Hole Spacing



## RF Connectors Technical Data Sheet

ET11262

### **Material Specifications**

Description	Material	Plating
Contact	Beryllium Copper	Gold over Nickel MIL-G-45204
Insulation	PTFE	
Outer Conductor	Stainless Steel	Gold MIL-G-45204
Body	Stainless Steel	Gold MIL-G-45204

# Environmental Specifications

#### Temperature

Operating Range Vibration Salt Spray

-55 to +100 deg C MIL-STD-202, Method 204, Condition D (20 G's) MIL-STD-202, Method 101, Condition B, 5% salt solution

Compliance Certifications (see product page for current document)

### Plotted and Other Data

Notes:

#### **Assembly Instruction**

SMA Female Connector Solder Attachment Thru Hole PCB, .200 inch x .067 inch Hole Spacing from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female Connector Solder Attachment Thru Hole PCB, .200 inch x .067 inch Hole Spacing ET11262

**URL:** https://www.ebeestock.com/sma-female-connector-solder-attachment-thru-hole-pcb-200-inch-x-067-inch-hole-spacing-0011262

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

