

SMA Male Connector Crimp/Solder Attachment for ET38362, ET38 397, 0.240 inch, ET38379, ET38379-DB, ET38379-UF, B7808A



RF Connectors Technical Data Sheet

ET11270

Configuration

- SMA Male Connector
- 50 Ohms
- Straight Body Geometry
- ET38362, ET38397, 0.240 inch, ET38379, ET38374,

ET38373, B7808A Interface Type

- Crimp/Solder Attachment
- 5/16 inch Hex

Features

• Max. Operating Frequency 12.4 GHz

Gold Plated Brass Contact

Applications

General Purpose Test

Custom Cable Assemblies

Description

Ebeestock's ET11270 SMA male connector with crimp/solder attachment for ET38362, ET38397, 0.240 inch, ET38379, LMR- 240-DB, ET38373 and B7808A is part of our full line of RF components available for same-day shipping. Our SMA male connector operates up to a maximum frequency of 12.4 GHz.

Our SMA male connector ET11270 datasheet specifications and drawing with dimensions are shown below in this PDF. Ebeestock's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Ebeestock has the right connector for the job. Ebeestock can also expertly build your custom cable assemblies for you and ship same-day.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		12.4	GHz
Operating Voltage (AC)			333	Vrms
Dielectric Withstanding Voltage (AC)			1,000	Vrms

Mechanical Specifications

Size

 Length
 0.969 in [24.61 mm]

 Width/Dia.
 0.312 in [7.92 mm]

 Weight
 0.014 lbs [6.35 g]

Mating Cycles 500 Cycles

Mating Torque 3 to 5 in-lbs [0.34 to 0.57 Nm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male Connector Crimp/Solder Attachment for ET38362, ET38397, 0.240 inch, ET38379, ET38374, ET38373, B7808A ET11270

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



SMA Male Connector Crimp/Solder Attachment for ET38362, ET38 397, 0.240 inch, ET38379, ET38379-DB, ET38379-UF, B7808A



RF Connectors Technical Data Sheet

ET11270

Material Specifications

Description	Material	Plating
Contact	Brass	Gold
Insulation	PTFE	
Body	Brass	Gold
Coupling Nut	Brass	Gold

Environmental Specifications

Temperature

Operating Range

-65 to +165 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

SMA Male Connector Crimp/Solder Attachment for ET38362, ET38397, 0.240 inch, ET38379, ET38374, ET38373, B7808A from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male Connector Crimp/Solder Attachment for ET38362, ET38397, 0.240 inch, ET38379, LMR- 240-DB, ET38373, B7808A ET11270


URL: https://www.ebeestock.com/sma-male-connector-crimp-solder-attachment-for-pe-c240-rg8x-0-24 0-inch-lmr-240-lmr-240-db-lmr-240-uf-b7808a-0011270

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.

ET11270 CAD Drawing

SMA Male Connector Crimp/Solder Attachment for ET38362, ET38397,



ET11270 REV 1.3