

SMA Male Right Angle Connector Crimp/Solder Attachment for E T38362, ET38397, .240 inch, ET38379, ET38379-DB, ET38379-UF, B7808A



# RF Connectors Technical Data Sheet

ET11271

#### Configuration

- SMA Male Connector
- 50 Ohms
- Right Angle Body Geometry

- Connector Interface Types: ET38362, ET38397, .240 inch, ET38379, ET38374, ET38373, B7808A
- 5/16 inch Hex

#### Features

- Max. Operating Frequency 12.4 GHz
- Gold Plated Brass Contact

• 50 µin minimum contact plating

### Applications

General Purpose Test

Custom Cable Assemblies

#### Description

Ebeestock's ET11271 SMA male right angle connector with crimp/solder attachment for ET38362, ET38397, .240 inch, LMR- 240, ET38374, ET38373 and B7808A is part of our full line of RF components available for same-day shipping. Our SMA male connector operates up to a maximum frequency of 12.4 GHz. Its right angle body geometry allows for easier connections in tight spaces.

Our SMA male right angle connector ET11271 datasheet specifications and drawing with dimensions are shown below in this PDF. Ebeestock's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Ebeestock has the right connector for the job. Ebeestock can also expertly build your custom cable assemblies for you and ship same-day.

#### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		12.4	GHz

#### Mechanical Specifications

Size	
Length	0.91 in [23.11 mm]
Width/Dia.	0.379 in [9.63 mm]
Height	0.715 in [18.16 mm]

Weight 0.023 lbs [10.43 g]

Mating Torque 3 to 5 in-lbs [0.34 to 0.57 Nm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male Right Angle Connector Crimp/Solder Attachment for ET38362, ET38397, .240 inch, ET38379, ET38374, ET38373, B7808A ET11271

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



SMA Male Right Angle Connector Crimp/Solder Attachment for E T38362, ET38397, .240 inch, ET38379, ET38379-DB, ET38379-UF, B7808A



## RF Connectors Technical Data Sheet

ET11271

#### **Material Specifications**

Description	Material	Plating
Contact	Brass	Gold 50 µin minimum
Insulation	PTFE	
Body	Brass	Gold 3 µin minimum
Coupling Nut	Brass	Gold 3 µin minimum

### **Environmental Specifications**Temperature

Operating Range

-65 to +165 deg C

Compliance Certifications (see product page for current document)

#### Plotted and Other Data

Notes:

SMA Male Right Angle Connector Crimp/Solder Attachment for ET38362, ET38397, .240 inch, ET38379, ET38374, ET38379-UF, B7808A from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male Right Angle Connector Crimp/Solder Attachment for ET38362, ET38397, .240 inch, LMR- 240, ET38374, ET38373, B7808A ET11271

**URL:** https://www.ebeestock.com/sma-male-right-angle-connector-crimp-solder-attachment-for-pe-c2 40-rg8x-240-inch-lmr-240-lmr-240-db-lmr-240-uf-b7808a-0011271

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.









