


SMA Male Connector Solder Attachment for ET38338, ET38337, E T38337J, ET38334, ET-RG402



# RF Connectors Technical Data Sheet

ET11280

# Configuration

- SMA Male Connector
- 50 Ohms
- Straight Body Geometry
- ET38338, ET38337, ET38335, ET-

### SR402TN, ET-RG402 Interface Type

- Solder Attachment
- 5/16 inch Hex

# Features

Max. Operating Frequency 18 GHz

# Applications

General Purpose Test

Custom Cable Assemblies

#### Description

Ebeestock's ET11280 SMA male connector with solder attachment for ET38338, ET38337, ET38335, ET- SR402TN and ET-RG402 is part of our full line of RF components available for same-day shipping. Our SMA male connector operates up to a maximum frequency of 18 GHz.

Our SMA male connector ET11280 datasheet specifications and drawing with dimensions are shown below in this PDF. Ebeestock's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Ebeestock has the right connector for the job. Ebeestock can also expertly build your custom cable assemblies for you and ship same-day.

#### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		18	GHz

# Mechanical Specifications

Size	
Length	0.441 in [11.2 mm]
Width/Dia.	0.315 in [8.00 mm]
Weight	0.005 lbs [2.27 g]
Mating Torque	8 to 10 in-lbs [0.90 to 1.13 Nm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male Connector Solder Attachment for ET38338, ET38337, ET38335, ET- SR402TN, ET-RG402 ET11280

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



SMA Male Connector Solder Attachment for ET38338, ET38337, E T38337J, ET38334, ET-RG402



# RF Connectors Technical Data Sheet

ET11280

#### Material Specifications

Description	Material	Plating
Body	Brass	Gold over Nickel
Coupling Nut	Passivated Stainless Steel	

Compliance Certifications (see product page for current document)

# Plotted and Other Data

Notes:

SMA Male Connector Solder Attachment for ET38338, ET38337, ET38335, ET38334, ET-RG402 from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male Connector Solder Attachment for ET38338, ET38337, ET38335, ET- SR402TN, ET-RG402 ET11280

**URL:** https://www.ebeestock.com/sma-male-connector-solder-attachment-for-pe-sr402al-pe-sr402fl-pe-sr402fl-pe-sr402flj-pe-sr402tn-rg402-0011280

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

ET11280 CAD Drawing
SMA Male Connector Solder Attachment for ET38338, ET-SR402FL, ET38335, ET38334, ET-RG402

