

SMA Female Field Replaceable Connector 4 Hole Flange Mount.

036 inch Pin, .500 inch Flange Size



RF Connectors Technical Data Sheet

ET11306

Configuration

- SMA Female Connector
- MIL-STD-348
- 50 Ohms

- Straight Body Geometry
- Connector Interface Types: .036 inch Pin
- 4 Hole Flange

Features

- Max. Operating Frequency 26 GHz
- Excellent VSWR of 1.2:1

- Gold Plated Beryllium Copper Contact
- Contact plating according to ASTM B-488

Applications

- General Purpose Test
- Rack and Panel Mount Applications

Description

Ebeestock's ET11306 SMA female 4 hole flange mount field replaceable connector is part of our full line of RF components available for same-day shipping. Our SMA female connector operates up to a maximum frequency of 26 GHz and offers excellent VSWR of 1.2:1. This SMA 4 hole flange connector allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications. This field replaceable connector is easy to install or replace in the field.

Our SMA female 4 hole flange connector ET11306 datasheet specifications and drawing with dimensions are shown below in this PDF. Ebeestock's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Ebeestock has the right connector for the job. Ebeestock can also expertly build your custom cable assemblies for you and ship same-day.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		26	GHz
VSWR			1.2:1	
Insertion Loss			0.15	dB
Operating Voltage (DC)			335	Vdc
Dielectric Withstanding Voltage (AC)			1,000	Vrms
Insulation Resistance	5,000			MOhms

Mechanical Specifications

Size

 Length
 0.5 in [12.7 mm]

 Width/Dia.
 0.5 in [12.70 mm]

 Height
 0.375 in [9.53 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female Field Replaceable Connector 4 Hole Flange Mount .036 inch Pin, .500 inch Flange Size ET11306

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



SMA Female Field Replaceable Connector 4 Hole Flange Mount . 036 inch Pin, .500 inch Flange Size



RF Connectors Technical Data Sheet

ET11306

Weight 0.001 lbs [0.45 g]

Mating Cycles

Mating Torque 2 in-lbs [0.23 Nm]

Material Specifications

Description	Material	Plating	
Contact	Beryllium Copper	Gold ASTM B-488	
Insulation	PTFE		
Body	Passivated Stainless Steel	ASTM A-967	

Environmental Specifications

Temperature

Operating Range

-65 to +165 deg C

Humidity

Mil-Std-202, Method 106

Mil-Std-202, Method 213, Test Cond. I.

Wibrotion

Vibration Mil-Std-202, Method 204, Test Cond. D. Salt Spray Mil-Std-202, Method 101, Test Cond. B.

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

SMA Female Field Replaceable Connector 4 Hole Flange Mount .036 inch Pin, .500 inch Flange Size from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female Field Replaceable Connector 4 Hole Flange Mount .036 inch Pin, .500 inch Flange Size ET11306

URL: https://www.ebeestock.com/sma-female-field-replaceable-connector-4-hole-flange-mount-036-i nch-pin-500-inch-flange-size-0011306

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.

ET11306 CAD Drawing

SMA Female Field Replaceable Connector 4 Hole Flange Mount .036 inch Pin, .500 inch Flange Size

