

SMA Male Connector Solder Attachment Thru Hole PCB, .200 inch x .067 inch Hole Spacing



RF Connectors Technical Data Sheet ET11331

Configuration

- SMA Male Connector
- MIL-STD-348A
- 50 Ohms
- Straight Body Geometry

Features

- Max. Operating Frequency 18 GHz
- Good VSWR of 1.3:1

- Thru Hole Interface Type
- Solder Attachment
- 5/16 inch Hex
- Gold Plated Brass Contact
- 30 µin minimum contact plating

Applications

General Purpose Test

PCB Applications

Description

Ebeestock's ET11331 SMA male connector with solder attachment for thru hole PCB (.200 inch x .067 inch hole spacing) is part of our full line of RF components available for same-day shipping. Our SMA male connector operates up to a maximum frequency of 18 GHz and offers good VSWR of 1.3:1.

Our SMA male connector ET11331 datasheet specifications and drawing with dimensions are shown below in this PDF. Ebeestock's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Ebeestock has the right connector for the job. Ebeestock can also expertly build your custom cable assemblies for you and ship same-day.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		18	GHz
VSWR			1.3:1	
Operating Voltage (AC)			500	Vrms

Mechanical Specifications

Size

 Length
 0.65 in [16.51 mm]

 Width/Dia.
 0.315 in [8.00 mm]

 Weight
 0.012 lbs [5.44 g]

Mating Torque 3 to 5 in-lbs [0.34 to 0.57 Nm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male Connector Solder Attachment Thru Hole PCB, .200 inch x .067 inch Hole Spacing ET11331

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



SMA Male Connector Solder Attachment Thru Hole PCB, .200 inch x .067 inch Hole Spacing



RF Connectors Technical Data Sheet ET11331

Material Specifications

Description	Material	Plating
Contact	Brass	Gold 30 µin minimum
Insulation	PTFE	
Body	Brass	Gold 3 µin minimum
Coupling Nut	Brass	Gold 3 µin minimum

Environmental SpecificationsTemperature

Operating Range

-65 to +165 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

SMA Male Connector Solder Attachment Thru Hole PCB, .200 inch x .067 inch Hole Spacing from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male Connector Solder Attachment Thru Hole PCB, .200 inch x .067 inch Hole Spacing ET11331

URL: https://www.ebeestock.com/sma-male-connector-solder-attachment-thru-hole-pcb-200-inch-x-06 7-inch-hole-spacing-0011331

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

ET11331 CAD Drawing
SMA Male Connector Solder Attachment Thru Hole PCB, .200 inch x .067 inch Hole Spacing

