

SMA Female Bulkhead Mount Connector Solder Attachment for ET 38338, ET38337, ET38337J, ET38334, ET-RG402, .235 inch D Hole



RF Connectors Technical Data Sheet

ET11376

Configuration

- SMA Female Connector
- MIL-STD-348A
- 50 Ohms
- Straight Body Geometry

- Connector Interface Types: ET38338, ET-SR-402FL, ET38335, ET38334, ET-RG402
- Bulkhead

Features

- Max. Operating Frequency 6 GHz
- Excellent VSWR of 1.23:1

- Gold Plated Beryllium Copper Contact
- 50 µin minimum contact plating

Applications

General Purpose Test

- Rack and Panel Mount Applications
- Custom Cable Assemblies

Description

Ebeestock's ET11376 SMA female bulkhead connector with solder/solder attachment for ET38338, ET38337, ET-SR402FLJ, ET38334 and ET-RG402 (.235 inch D hole) is part of our full line of RF components available for same-day shipping. Our SMA female connector operates up to a maximum frequency of 6 GHz and offers excellent VSWR of 1.23:1. This SMA bulkhead connector allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

Our SMA female bulkhead connector ET11376 datasheet specifications and drawing with dimensions are shown below in this PDF. Ebeestock's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Ebeestock has the right connector for the job. Ebeestock can also expertly build your custom cable assemblies for you and ship same-day.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		6	GHz
VSWR			1.23:1	
Operating Voltage (AC)			500	Vrms

Mechanical Specifications

Size

 Length
 0.748 in [19 mm]

 Width/Dia.
 0.433 in [11.00 mm]

 Height
 0.433 in [11 mm]

 Weight
 0.009 lbs [4.08 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female Bulkhead Mount Connector Solder Attachment for ET38338, ET38337, ET38335, ET38334, ET-RG402, .235 inch D Hole ET11376

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



SMA Female Bulkhead Mount Connector Solder Attachment for ET 38338, ET38337, ET38337J, ET38334, ET-RG402, .235 inch D Hole



RF Connectors Technical Data Sheet

ET11376

Material Specifications

Description	Material	Plating
Contact	Beryllium Copper	Gold 50 µin minimum
Insulation	PTFE	
Body	Stainless Steel	Gold 30 µin minimum
Washer	Brass	Gold 30 µin minimum

Environmental SpecificationsTemperature

Operating Range

-65 to +165 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

SMA Female Bulkhead Mount Connector Solder Attachment for ET38338, ET38337, ET38335, ET38334, ET-RG402, .235 inch D Hole from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female Bulkhead Mount Connector Solder Attachment for ET38338, ET38337, ET-SR402FLJ, ET38334, ET-RG402, .235 inch D Hole ET11376

URL: https://www.ebeestock.com/sma-female-bulkhead-mount-connector-solder-attachment-for-pe-sr4 02al-pe-sr402fl-pe-sr402flj-pe-sr402tn-rg402-235-inch-d-hole-0011376

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.

