

RP SMA Female Connector Solder Attachment Thru Hole PCB, .20 0 inch x .067 inch Hole Spacing



RF Connectors Technical Data Sheet ET11469

Configuration

- SMA Female Reverse Polarity Connector
- MIL-STD-348
- 50 Ohms

Features

- Max. Operating Frequency 12 GHz
- Gold Plated Contact

- Straight Body Geometry
- Thru Hole Interface Type
- Solder Attachment
- Contact plating according to MIL-G-45204
- Reverse Polarity

Applications

General Purpose Test

PCB Applications

Description

Ebeestock's ET11469 RP SMA female connector with solder attachment for thru hole PCB (.200 inch x .067 inch hole spacing) is part of our full line of RF components available for same-day shipping. The female reverse polarity configuration uses a female connector body with a male inner contact pin. Our SMA female connector operates up to a maximum frequency of 12 GHz.

Our reverse polarity SMA female connector ET11469 datasheet specifications and drawing with dimensions are shown below in this PDF. Ebeestock's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Ebeestock has the right connector for the job. Ebeestock can also expertly build your custom cable assemblies for you and ship same-day.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		12	GHz
Operating Voltage (AC)			500	Vrms
Dielectric Withstanding Voltage (AC)			1,000	Vrms
Insulation Resistance	5,000			MOhms

Mechanical Specifications

Size

 Length
 0.5 in [12.7 mm]

 Width/Dia.
 0.25 in [6.35 mm]

 Height
 0.25 in [6.35 mm]

 Weight
 0.004 lbs [1.81 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: RP SMA Female Connector Solder Attachment Thru Hole PCB, .200 inch x .067 inch Hole Spacing ET11469

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



RP SMA Female Connector Solder Attachment Thru Hole PCB, .20 0 inch x .067 inch Hole Spacing



RF Connectors Technical Data Sheet ET11469

Material Specifications

Description	Material	Plating
Contact		Gold MIL-G-45204
Insulation	PTFE	
Body	Brass	Gold MIL-G-45204

Environmental Specifications

Temperature

Operating Range

-65 to +165 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

RP SMA Female Connector Solder Attachment Thru Hole PCB, .200 inch x .067 inch Hole Spacing from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: RP SMA Female Connector Solder Attachment Thru Hole PCB, .200 inch x .067 inch Hole Spacing ET11469

URL: https://www.ebeestock.com/rp-sma-female-connector-solder-attachment-thru-hole-pcb-200-inch-x-067-inch-hole-spacing-0011469

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.

