

SMP Male Full Detent Hermetically Sealed Connector Solder At tachment Pin Terminal, Full Shroud Full Body, Up To 8 GHz



RF Connectors Technical Data Sheet

ET11512

Configuration

- Full Detent SMP Male Connector
- MIL-STD-348A
- 50 Ohms

Features

- Max. Operating Frequency 8 GHz
- Excellent VSWR of 1.1:1
- Gold Plated Kovar Contact

- Straight Body Geometry
- Pin Interface Type
- Solder Attachment
- Blind Mate Connector
- Hermetically Sealed

Applications

General Purpose Test

Description

Ebeestock's ET11512 SMP male full detent hermetically sealed connector with solder attachment pin terminal is part of our full line of RF components available for same-day shipping. Our SMP male connector operates up to a maximum frequency of 8 GHz and offers excellent VSWR of 1.1:1. The Ebeestock blind mate connector is ideal for applications where direct visual or tactile access to the connection point is not possible, for example, when two circuit boards need to be mated.

Our SMP male connector ET11512 datasheet specifications and drawing with dimensions are shown below in this PDF. Ebeestock's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Ebeestock has the right connector for the job. Ebeestock can also expertly build your custom cable assemblies for you and ship same-day.

Electrical Specifications

Minimum	Typical	Maximum	Units
DC		8	GHz
		1.1:1	
		335	Vrms
		500	Vrms
		6	mOhms
		2	mOhms
5,000			MOhms
	DC	DC	DC 8 1.1:1 335 500 6 2

Electrical Specification Notes:

Insertion loss = $0.13 \times \text{sqrt(fGHz)} dB \text{ max.}$

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMP Male Full Detent Hermetically Sealed Connector Solder Attachment Pin Terminal, Full Shroud Full Body, Up To 8 GHz ET11512

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



SMP Male Full Detent Hermetically Sealed Connector Solder At tachment Pin Terminal, Full Shroud Full Body, Up To 8 GHz



RF Connectors Technical Data Sheet

ET11512

Mechanical Specifications

Size

 Length
 0.25 in [6.35 mm]

 Width/Dia.
 0.165 in [4.19 mm]

 Weight
 0.005 lbs [2.27 g]

 Mating Cycles
 100 Cycles

Material Specifications

Description	Material	Plating	
Contact	Kovar	Gold	
Insulation	Glass		
Body	Kovar	Gold	

Environmental Specifications

Temperature

Operating Range -65 to +165 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

SMP Male Full Detent Hermetically Sealed Connector Solder Attachment Pin Terminal, Full Shroud Full Body, Up To 8 GHz from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMP Male Full Detent Hermetically Sealed Connector Solder Attachment Pin Terminal, Full Shroud Full Body, Up To 8 GHz ET11512

URL: https://www.ebeestock.com/smp-male-full-detent-hermetically-sealed-connector-solder-attach ment-pin-terminal-full-shroud-full-body-up-to-8-ghz-0011512

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.

ET11512 CAD Drawing

SMP Male Full Detent Hermetically Sealed Connector Solder Attachment Pin Terminal, Full Shroud Full Body, Up To 8 GHz

