


SMP Male Full Detent 2 Hole Flange Mount, .354 inch Hole Spacing



TECHNICAL DATA SHEET

ET11549

Configuration

Connector SMP Male, Full Detent

Connector Specification MIL-STD-348

Connector Interface Type
Attachment Method (Shield/Contact)

Body Style

None
Straight

Mount Method 2 Hole Flange

Electrical Specifications

Impedance 50 Ohms

Mechanical Specifications

Size

 Length
 0.48 in [12.19 mm]

 Width/Dia.
 0.176 in [4.47 mm]

 Height
 0.12 in [3.05 mm]

 Weight
 0.082 lbs [37.19 g]

Connector

Type SMP Male

Body Material and Plating Passivated Stainless Steel

Body Plating Specification AMS-QQ-P-35

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMP Male Full Detent Shroud 2 Hole Flange Mount 0.354 Inch Hole Spacing ET11549



SMP Male Full Detent 2 Hole Flange Mount, .354 inch Hole Spacing



TECHNICAL DATA SHEET

ET11549

Plotted and Other Data

Notes:

Values at +25 °C, sea level

SMP Male Full Detent Shroud 2 Hole Flange Mount 0.354 Inch Hole Spacing from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMP Male Full Detent Shroud 2 Hole Flange Mount 0.354 Inch Hole Spacing ET11549

URL: https://www.ebeestock.com/smp-male-full-detent-2-hole-flange-mount-354-inch-hole-spacing-0 011549

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

