

RP TNC Female Connector Crimp/Solder Attachment for ET38362, ET38397, 0.240 inch, ET38379, ET38379-DB, ET38379-UF, B7808A



RF Connectors Technical Data Sheet

ET11733

Configuration

- TNC Female Reverse Polarity Connector
- 50 Ohms
- Straight Body Geometry

- ET38362, ET38397, 0.240 inch, ET38379, ET38374, ET38373, B7808A Interface Type
- Crimp/Solder Attachment

Features

- Max. Operating Frequency 11 GHz
- Gold Plated Brass Contact

Reverse Polarity

Applications

- General Purpose Test
- Custom Cable Assemblies

Description

Ebeestock's ET11733 RP TNC female connector with crimp/solder attachment for ET38362, ET38397, 0.240 inch, ET38379, ET38374, ET38373 and B7808A is part of our full line of RF components available for same-day shipping. The female reverse polarity configuration uses a female connector body with a male inner contact pin. Our TNC female connector operates up to a maximum frequency of 11 GHz.

Our reverse polarity TNC female connector ET11733 datasheet specifications and drawing with dimensions are shown below in this PDF. Ebeestock's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Ebeestock has the right connector for the job. Ebeestock can also expertly build your custom cable assemblies for you and ship same-day.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		11	GHz

Mechanical Specifications

Size

 Length
 1.325 in [33.66 mm]

 Width/Dia.
 0.453 in [11.51 mm]

 Weight
 0.026 lbs [11.79 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: RP TNC Female Connector Crimp/Solder Attachment for ET38362, ET38397, 0.240 inch, LMR- 240, ET38374, ET38373, B7808A ET11733

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



RP TNC Female Connector Crimp/Solder Attachment for ET38362, ET38397, 0.240 inch, ET38379, ET38379-DB, ET38379-UF, B7808A



RF Connectors Technical Data Sheet

ET11733

Material Specifications

Description	Material	Plating
Contact	Brass	Gold
Insulation	PTFE	
Body	Brass	Nickel

Environmental Specifications

Temperature

Operating Range

-65 to +165 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

RP TNC Female Connector Crimp/Solder Attachment for ET38362, ET38397, 0.240 inch, ET38379, ET38374, ET38373, B7808A from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: RP TNC Female Connector Crimp/Solder Attachment for ET38362, ET38397, 0.240 inch, ET38379, ET38374, ET38373, B7808A ET11733

URL: https://www.ebeestock.com/rp-tnc-female-connector-crimp-solder-attachment-for-pe-c240-rg8x -0-240-inch-lmr-240-lmr-240-db-lmr-240-uf-b7808a-0011733

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



