

TNC Male Connector Crimp/Crimp Attachment for ET38356, ET383 69, With POM Insulator



RF Connectors Technical Data Sheet

ET11748

Configuration

- TNC Male Connector
- 50 Ohms
- Straight Body Geometry

- ET38356, ET38369 Interface Type
- Crimp/Crimp Attachment

Features

Max. Operating Frequency 11 GHz

Gold Plated Brass Contact

Applications

General Purpose Test

Custom Cable Assemblies

Description

Ebeestock's ET11748 TNC male connector with crimp/crimp attachment for ET38356 and ET38369 is part of our full line of RF components available for same-day shipping. Our TNC male connector operates up to a maximum frequency of 11 GHz.

Our TNC male connector ET11748 datasheet specifications and drawing with dimensions are shown below in this PDF. Ebeestock's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Ebeestock has the right connector for the job. Ebeestock can also expertly build your custom cable assemblies for you and ship same-day.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		11	GHz

Mechanical Specifications

Size

 Length
 0.981 in [24.92 mm]

 Width/Dia.
 0.571 in [14.50 mm]

 Weight
 0.03 lbs [13.61 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: TNC Male Connector Crimp/Crimp Attachment for ET38356, ET38369, With POM Insulator ET11748

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



TNC Male Connector Crimp/Crimp Attachment for ET38356, ET383 69, With POM Insulator



RF Connectors Technical Data Sheet

ET11748

Material Specifications

Description	Material	Plating
Contact	Brass	Gold
Insulation	POM	
Body	Brass	Nickel
Coupling Nut	Brass	Nickel

Environmental Specifications

Temperature

Operating Range

-40 to +85 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

TNC Male Connector with POM Insulator Crimp/Crimp Attachment For ET38356, ET38369 from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: TNC Male Connector Crimp/Crimp Attachment for ET38356, ET38369, With POM Insulator ET11748

URL: https://www.ebeestock.com/tnc-male-connector-crimp-crimp-attachment-for-pe-c200-lmr-200-wi th-pom-insulator-0011748

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

