

RP-TNC Male Connector Crimp/Solder Attachment for ET-RG58



RF Connectors Technical Data Sheet

ET11787

Configuration

- TNC Male Reverse Polarity Connector
- 50 Ohms

- Straight Body Geometry
- Connector Interface Types: ET-RG58

Features

- Max. Operating Frequency 10 GHz
- Gold Plated Brass Contact

- 30 µinches minimum contact plating
- Reverse Polarity

Applications

- General Purpose Test
- Custom Cable Assemblies

Description

Ebeestock's ET11787 RP TNC male connector with crimp/solder attachment for ET-RG58 is part of our full line of RF components available for same-day shipping. The male reverse polarity configuration uses a male connector body with a female inner contact receptacle. Our TNC male connector operates up to a maximum frequency of 10 GHz.

Our reverse polarity TNC male connector ET11787 datasheet specifications and drawing with dimensions are shown below in this PDF. Ebeestock's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Ebeestock has the right connector for the job. Ebeestock can also expertly build your custom cable assemblies for you and ship same-day.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		10	GHz
Operating Voltage (AC)			500	Vrms

Mechanical Specifications

Size

Length
Width/Dia.

1.135 in [28.83 mm]
0.571 in [14.50 mm]
Weight

0.034 lbs [15.42 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: RP-TNC Male Connector Crimp/Solder Attachment for ET-RG58 ET11787

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



RP-TNC Male Connector Crimp/Solder Attachment for ET-RG58



RF Connectors Technical Data Sheet

ET11787

Material Specifications

Description	Material	Plating
Contact	Brass	Gold 30 µinches minimum
Body	Brass	Nickel 100 µinches minimum

Environmental Specifications

Temperature

Operating Range

-65 to +165 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

RP-TNC Male Connector Crimp/Solder Attachment for ET-RG58 from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: RP-TNC Male Connector Crimp/Solder Attachment for ET-RG58 ET11787

URL: https://www.ebeestock.com/rp-tnc-male-connector-crimp-solder-attachment-for-rg58-0011787

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.

