

RP TNC Male Connector Clamp/Solder Attachment for ET-RG59, E T-ET-RG62, ET-RG71



RF Connectors Technical Data Sheet

ET11788

Configuration

- TNC Male Reverse Polarity Connector
- 50 Ohms

- Straight Body Geometry
- Connector Interface Types: ET-RG59, ET-RG62, ET-RG71

Features

- Max. Operating Frequency 11 GHz
- Gold Plated Brass Contact

Reverse Polarity

Applications

General Purpose Test

Custom Cable Assemblies

Description

Ebeestock's ET11788 RP TNC male connector with clamp/solder attachment for ET-RG59, ET-RG62 and ET-RG71 is part of our full line of RF components available for same-day shipping. The male reverse polarity configuration uses a male connector body with a female inner contact receptacle. Our TNC male connector operates up to a maximum frequency of 11 GHz.

Our reverse polarity TNC male connector ET11788 datasheet specifications and drawing with dimensions are shown below in this PDF. Ebeestock's broad catalog of RF, microwave and millimeter wave connectors allows designers to configure and customize their signal connections however they like. Whether the need is to provide an I/O for a board design, or simply create a custom cable assembly configuration, Ebeestock has the right connector for the job. Ebeestock can also expertly build your custom cable assemblies for you and ship same-day.

FI	ectrical	Specifications	
	COLICA	Deciloano	

Frequency Range	DC		11	GHz
Operating Voltage (AC)			500	Vrms

Mechanical Specifications

Size

Length
Width/Dia.

1.05 in [26.67 mm]
0.571 in [14.50 mm]
Weight

0.044 lbs [19.96 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: RP TNC Male Connector Clamp/Solder Attachment for ET-RG59, ET-RG62, ET-RG71



RP TNC Male Connector Clamp/Solder Attachment for ET-RG59, E T-ET-RG62, ET-RG71



RF Connectors ET11788



RP TNC Male Connector Clamp/Solder Attachment for ET-RG59, E T-ET-RG62, ET-RG71



RF Connectors Technical Data Sheet

ET11788

Material Specifications

Description	Material	Plating
Contact	Brass	Gold
Insulation	PTFE	
Body	Brass	Nickel 100 µin minimum
Coupling Nut	Brass	Nickel 100 µin minimum

Mechanical Specification Notes:

When attaching the connector to the cable use a clamp torque value of 26 to 30 in-lbs [2.94 to 3.39 Nm]

Environmental Specifications

Temperature

Operating Range

-65 to +165 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

RP TNC Male Connector Clamp/Solder Attachment for ET-RG59, ET-RG62, ET-RG71 from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: RP TNC Male Connector Clamp/Solder Attachment for ET-RG59, ET-RG62, ET-RG71

URL: https://www.ebeestock.com/rp-tnc-male-connector-clamp-solder-attachment-for-rg59-rg62-rg71 -0011788

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.

ET11788 CAD Drawing

RP TNC Male Connector Clamp/Solder Attachment for ET-RG59, ET-RG62, ET-RG71

