

SMA Male to 1.0/2.3 Plug Adapter



RF Adapters Technical Data Sheet

ET1185

8

Configuration

- SMA Male Connector 1
- 1.0/2.3 Plug Connector 2

- 50 Ohms
- Straight Body Geometry

Features

- SMA Interface compliant with MIL-STD-348
- 1.0/2.3 Interface compliant with MIL-C-39012
- Gold Plated Contact
- Contact Plating per MIL-G-45204

Applications

- Allows Connection Between Series
- General Purpose Test

Description

Ebeestock's ET11858 SMA male to 1.0/2.3 plug adapter is part of our full line of RF components available for same-day shipping. The SMA connector mates mechanically with commercially available 3.5mm and 2.92mm (K) connectors. Our SMA to 1.0/2.3 adapter has a male to plug gender configuration.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Mechanical Specifications

Size Length Width Weight	0.872 in [22.18 0.312 in [7.92 0.011 lbs [4.99	mm]
Туре	SMA Male	1.0/2.3 Plug
Polarity	Standard	Standard
Interface Specification	MIL-STD-348	MIL-C-39012
Hex Size	5/16 in.	
Mating Torque	3 to 5 in-lbs [0.34 to 0.57 Nm]	

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male to 1.0/2.3 Plug Adapter ET11858



SMA Male to 1.0/2.3 Plug Adapter



RF Adapters Technical Data Sheet ET11858

Material Specifications

	Conn	ector 1	Conn	ector 2
Description	Material	Plating	Material	Plating
Туре	SMA Male		1.0/2.3 Plug	
Contact		Gold		Gold
		MIL-G-45204		MIL-G-45204
Insulation	PTFE		PTFE	
Body	Brass	Nickel	Brass	Nickel
		QQ-N-290		QQ-N-290
Coupling Nut	Brass	Nickel		
		QQ-N-290		

Environmental Specifications

Temperature

Operating Range

-65 to +165 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:


SMA Male to 1.0/2.3 Plug Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male to 1.0/2.3 Plug Adapter ET11858

URL: https://www.ebeestock.com/sma-male-to-1-0-2-3-plug-adapter-0011858

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

ET11858 CAD Drawing SMA Male to 1.0/2.3 Plug Adapter



ebeestock.com	PWG TITLE FT11858	NOTES: 1. UNLESS OTHER! 2. ALL SPECIFICAT 3. DIMENSIONS AR	TES: UNLESS OTHERWISE SPECIFIED AL ALL SPECIFICATIONS ARE SUBJEC DIMENSIONS ARE IN INCHES [mm].	ALL DIMENSIONS ARE NOMINAL. CT TO CHANGE WITHOUT NOTICE AT].	NOMINAL. OT NOTICE AT	ANY TIME.
8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park						
, Humen,523900, Do	REV	FSCM NO. 53919	CAD FILE 101502	SCALE N/A	SIZE A	127