

2.4mm Female to 1.85mm Male Adapter



## RF Adapters Technical Data Sheet

ET1190

4

## Configuration

- 2.4mm Female Connector 1
- 1.85mm Male Connector 2

- 50 Ohms
- Straight Body Geometry

#### Features

- Max VSWR of 1.3:1 up to 50 GHz
- Gold over Nickel Plated Beryllium Copper Contact
- Contact Plating per MIL-G-45204

## Applications

• Allows Connection Between Series

General Purpose Test

## Description

Ebeestock's ET11904 2.4mm female to 1.85mm male adapter is part of our full line of RF components available for sameday shipping. The 2.4mm connector mates mechanically with commercially available 1.85mm (V) connectors. Our 2.4mm to 1.85mm adapter has a female to male gender configuration. ET11904 2.4mm female to 1.85mm male adapter operates to 50 GHz. The Ebeestock RF adapter provides good VSWR of 1.3:1 maximum.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

ectrical Specifications			
Erequency Range	DC	50	GHz
VSWR		1.3:1	
Insertion Loss		0.36	dB

Electrical Specification Notes: Values at 25°C, sea level. Insertion Loss (dB) = 0.05\*sqrt(fGHz).

#### Mechanical Specifications

Size

 Length
 0.768 in [19.51 mm]

 Width
 0.312 in [7.92 mm]

 Weight
 0.013 lbs [5.9 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 2.4mm Female to 1.85mm Male Adapter ET11904

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



2.4mm Female to 1.85mm Male Adapter



## RF Adapters Technical Data Sheet ET11904

Connector 1	Connector 2
2.4mm Female	1.85mm Male
Standard	Standard
500	500
	5/16 in.
	8 to 10 in-lbs [0.90 to 1.13 Nm]
	2.4mm Female Standard

#### Material Specifications

	Connector 1		Connector 2	
Description	Material	Plating	Material	Plating
Туре	2.4mm Female		1.85mm Male	
Contact	Beryllium Copper	Gold over Nickel	Beryllium Copper	Gold over Nickel
		MIL-G-45204		MIL-G-45204
Insulation	Oxide-Noryl		Oxide-Noryl	
Outer Conductor Pa	assivated Stainless Steel			
		ASTM A380		
Body			Passivated Stainless Steel	
				ASTM A380
Coupling Nut			Passivated Stainless Steel	
				ASTM A380

### **Environmental Specifications**

Temperature

Operating Range -55 to +100 deg C

Vibration MIL-STD-202, Method 204, Cond. D (20G's)

Salt Spray MIL-STD-202, Method 101, Cond. B, 5% salt solution

Compliance Certifications (see product page for current document)

#### Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 2.4mm Female to 1.85mm Male Adapter ET11904



2.4mm Female to 1.85mm Male Adapter



# RF Adapters Technical Data Sheet ET11904

2.4mm Female to 1.85mm Male Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 2.4mm Female to 1.85mm Male Adapter ET11904

URL: https://www.ebeestock.com/2-4mm-female-to-1-85mm-male-adapter-0011904

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

# ET11904 CAD Drawing 2.4mm Female to 1.85mm Male Adapter

