

SMA Female to 1.85mm Female Adapter



## RF Adapters Technical Data Sheet

ET1190

9

## Configuration

- SMA Female Connector 1
- 1.85mm Female Connector 2

- 50 Ohms
- Straight Body Geometry

#### Features

- Max VSWR of 1.3:1 up to 18 GHz
- SMA Interface compliant with MIL-STD-348
- Gold Plated Beryllium Copper Contact

## Applications

• Allows Connection Between Series

General Purpose Test

#### Description

Ebeestock's ET11909 SMA female to 1.85mm female adapter is part of our full line of RF components available for sameday shipping. The SMA connector mates mechanically with commercially available 3.5mm and 2.92mm (K) connectors. The 1.85mm connector mates mechanically with commercially available 2.4mm connectors. Our SMA to 1.85mm adapter has a female to female gender configuration. ET11909 SMA female to 1.85mm female adapter operates to 18 GHz. The Ebeestock RF adapter provides good VSWR of 1.3:1 maximum.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications			
Erequency Range	DC	18	GHz
VSWR		1.3:1	

#### Mechanical Specifications

Size

Length
Width
Weight

0.895 in [22.73 mm]
0.28 in [7.11 mm]
0.011 lbs [4.99 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female to 1.85mm Female Adapter ET11909



SMA Female to 1.85mm Female Adapter



## RF Adapters Technical Data Sheet ET11909

Description	Connector 1	Connector 2
Туре	SMA Female	1.85mm Female
Polarity	Standard	Standard
Interface Specification	MIL-STD-348	
interface opecinication		

#### Material Specifications

Description	Connector 1		Connector 2	
	Material	Plating	Material	Plating
Туре	SMA Female		1.85mm Female	
Contact	Beryllium Copper	Gold	Beryllium Copper	Gold
Outer Conductor P	assivated Stainless Steel		Passivated Stainless Steel	

# Environmental Specifications

Temperature

Operating Range

-65 to +125 deg C

Compliance Certifications (see product page for current document)

#### Plotted and Other Data

Notes:

SMA Female to 1.85mm Female Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female to 1.85mm Female Adapter ET11909

URL: https://www.ebeestock.com/sma-female-to-1-85mm-female-adapter-0011909

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

# ET11909 CAD Drawing SMA Female to 1.85mm Female Adapter

