

2.92mm Male to 2.4mm Male Adapter



RF Adapters Technical Data Sheet

ET1197

3

Configuration

- 2.92mm Male Connector 1
- 2.4mm Male Connector 2

Features

- Max VSWR of 1.3:1 up to 40 GHz
- Gold Plated Beryllium Copper Contact

- 50 Ohm
- Straight Body Geometry
- Max VSWR of 1.3:1 up to 40 GHz
- Gold Plated Beryllium Copper Contact


Applications

- Allows Connection Between Series
- General Purpose Test
- Allows Connection Between Series
- General Purpose Test

Description

Ebeestock's ET11973 2.92mm male to 2.4mm male adapter is part of our full line of RF components available for same-day shipping. The 2.92mm connector mates mechanically with commercially available SMA and 3.5mm connectors. The 2.4mm connector mates mechanically with commercially available 1.85mm (V) connectors. Our 2.92mm to 2.4mm adapter has a male to male gender configuration built of durable stainless steel. ET11973 2.92mm male to 2.4mm male adapter operates to 40 GHz. The Ebeestock RF adapter provides good VSWR of 1.3:1 maximum.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.



Mechanical Specifications

Size

Length 0.81 in [20.57 mm]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 2.92mm Male to 2.4mm Male Adapter ET11973

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



2.92mm Male to 2.4mm Male Adapter



RF Adapters Technical Data Sheet ET11973

 Width
 0.312 in [7.92 mm]

 Weight
 0.0193 lbs [8.75 g]

Description	Connector 1	Connector 2	
Type	2.92mm Male	2.4mm Male	
Polarity	Standard	Standard	
Hex Size	5/16 in.	5/16 in.	

Material Specifications

Description	Connector 1		Connector 2	
	n Material	Plating	Material	Plating
Туре	2.92mm Male		2.4mm Male	
Contact	Beryllium Copper	Gold	Beryllium Copper	Gold
Body	Passivated Stainless Steel		Passivated Stainless Steel	

Environmental Specifications

Temperature

Operating Range -65 to +125 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 2.92mm Male to 2.4mm Male Adapter ET11973



2.92mm Male to 2.4mm Male Adapter




RF Adapters Technical Data Sheet ET11973


2.92mm Male to 2.4mm Male Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 2.92mm Male to 2.4mm Male Adapter ET11973

URL: https://www.ebeestock.com/2-92mm-male-to-2-4mm-male-adapter-0011973

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.





OMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.