

Precision SMA Female to 2.92mm Female Adapter



RF Adapters Technical Data Sheet

ET11988

Configuration

- SMA Female Connector 1
- 2.92mm Female Connector 2
- 50 Ohms

- Precision Design
- Straight Body Geometry

Features

- Max VSWR of 1.2:1 up to 26.5 GHz
- SMA Interface compliant with MIL-STD-348
- Gold over Nickel Plated Beryllium Copper Contact
- 50µ in min Gold over Nickel Contact Plating

Applications

- Allows Connection Between Series
- General Purpose Test
- Precision Test & Measurement

Description

Ebeestock's ET11988 precision SMA female to 2.92mm female adapter is part of our full line of RF components available for same-day shipping. The SMA connector mates mechanically with commercially available 3.5mm and 2.92mm (K) connectors. Our SMA to 2.92mm adapter has a female to female gender configuration in a precision design. ET11988 SMA female to 2.92mm female adapter operates to 26.5 GHz. The Ebeestock RF adapter provides excellent VSWR of 1.2:1 maximum.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		26.5	GHz
VSWR			1.2:1	
Insertion Loss			0.25	dB
Dielectric Withstanding Voltage (AC)			750	Vrms

Electrical Specification Notes: Values at 25°C, sea level.

Mechanical Specifications

Size

 Length
 0.722 in [18.34 mm]

 Width
 0.31 in [7.87 mm]

 Weight
 0.009 lbs [4.08 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Precision SMA Female to 2.92mm Female Adapter ET11988

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



Precision SMA Female to 2.92mm Female Adapter



RF Adapters Technical Data Sheet

ET11988

Description	Connector 1	Connector 2	
Туре	SMA Female	2.92mm Female	
Polarity	Standard	Standard	
Interface Specification	MIL-STD-348		

Material Specifications

	Connector 1		Connector 2		
Description	Material	Plating	Material	Plating	
Туре	SMA Female		2.92mm Female		
Contact	Beryllium Copper	Gold over Nickel	Beryllium Copper	Gold over Nickel	
		50 µin minimum		50 µin minimum	
Insulation	PTFE		PTFE		
Outer Conductor F	Passivated Stainless Steel		Passivated Stainless Steel		
		SAE-AMS-2700		SAE-AMS-2700	

Environmental Specifications Temperature

Temperature
Operating Range

-55 to +150 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Precision SMA Female to 2.92mm Female Adapter ET11988



Precision SMA Female to 2.92mm Female Adapter



RF Adapters Technical Data Sheet

ET11988

Precision SMA Female to 2.92mm Female Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Precision SMA Female to 2.92mm Female Adapter ET11988

URL: https://www.ebeestock.com/precision-sma-female-to-2-92mm-female-adapter-0011988

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

ET11988 CAD Drawing
Precision SMA Female to 2.92mm Female Adapter

