

Low PIM 7/16 DIN Female to 4.1/9.5 Mini DIN Male Adapter



RF Adapters Technical Data Sheet

ET12019

Configuration

- 7/16 DIN Female Connector 1
- 4.1/9.5 Mini DIN Male Connector 2
- 50 Ohms

- Low PIM Design
- Straight Body Geometry

Features

- Max VSWR of 1.25:1 up to 6 GHz
- PIM levels lower than -160 dBc

- Silver Plated Beryllium Copper Contact
- 5 µm min Silver Contact Plating

Applications

- Allows Connection Between Series
- General Purpose Test

Description

Ebeestock's ET12019 Low PIM 7/16 DIN female to 4.1/9.5 Mini DIN male adapter is part of our full line of RF components available for same-day shipping. Our 7/16 DIN to 4.1/9.5 Mini DIN adapter has a female to male gender configuration in a Low PIM design. ET12019 7/16 DIN female to 4.1/9.5 Mini DIN male adapter operates to 6 GHz. The Ebeestock RF adapter provides excellent VSWR of 1.25:1 maximum and passive intermodulation of -160 dBc maximum.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		6	GHz
VSWR			1.25:1	
Passive Intermodulation			-160	dBc
using 2x20W tones				
Operating Voltage (AC)			1,400	Vrms
Dielectric Withstanding Voltage (AC)			2,500	Vrms

Performance by Frequency

Description	F1	F2	F3	F4	F5	Units
Frequency Range	DC to 3	3 to 4	4 to 6			GHz
VSWR, Max	1.1:1	1.15:1	1.25:1			

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Low PIM 7/16 DIN Female to 4.1/9.5 Mini DIN Male Adapter ET12019



Low PIM 7/16 DIN Female to 4.1/9.5 Mini DIN Male Adapter



RF Adapters Technical Data Sheet

ET12019

Electrical Specification Notes: Values at 25°C, sea level.

Mechanical Specifications

Size

 Length
 2.03 in [51.56 mm]

 Width
 1.14 in [28.96 mm]

 Weight
 0.271 lbs [122.92 g]

Description	Connector 1	Connector 2
Туре	7/16 DIN Female	4.1/9.5 Mini DIN Male
Polarity	Standard	Standard
Hex Size		22 mm

Material Specifications

	Connector 1		Connector 2		
Description	Material	Plating	Material	Plating	
Гуре	7/16 DIN Female		4.1/9.5 Mini DIN Male		
Contact	Beryllium Copper	Silver	Beryllium Copper	Silver	
		5 µm minimum		5 µm minimum	
Insulation	PTFE		PTFE		
Outer Conductor	Brass	Tri-Metal			
		3 µm minimum			
Body			Brass	Tri-Metal	
				3 µm minimum	
Coupling Nut			Brass	Tri-Metal	
				3 µm minimum	

Environmental Specifications

Temperature

Operating Range

-40 to +120 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Low PIM 7/16 DIN Female to 4.1/9.5 Mini DIN Male Adapter ET12019

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



Low PIM 7/16 DIN Female to 4.1/9.5 Mini DIN Male Adapter



RF Adapters Technical Data Sheet

ET12019

Low PIM 7/16 DIN Female to 4.1/9.5 Mini DIN Male Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Low PIM 7/16 DIN Female to 4.1/9.5 Mini DIN Male Adapter ET12019

URL: https://www.ebeestock.com/low-pim-7-16-din-female-to-4-1-9-5-mini-din-male-adapter-0012019

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

ET12019 CAD Drawing
Low PIM 7/16 DIN Female to 4.1/9.5 Mini DIN Male Adapter

