

Low PIM 4.3-10 Male to 4.3-10 Male Adapter



RF Adapters Technical Data Sheet

ET12030

Configuration

- 4.3-10 Male Connector 1
- 4.3-10 Male Connector 2
- 50 Ohm

- Low PIM Design
- Straight Body Geometry

Features

- Max VSWR of 1.08:1 up to 6 GHz
- PIM levels lower than -166 dBc
- Silver Plated Bronze Contact

- Low Coupling Torque
- Corrosion Resistant Tri-Metal Finish

Applications

- General Purpose Test
- Low PIM Applications
- Mobile Communications Systems
- Base Stations
- Distributed Antenna Systems (DAS)
- Small Cells
- Feeder Cables

Description

Ebeestock's ET12030 4.3-10 male to 4.3-10 male adapter is part of our full line of RF components available for same-day shipping. Our 4.3-10 to 4.3-10 adapter has a male to male gender configuration in a low PIM design. ET12030 4.3-10 male to 4.3-10 male adapter operates to 6 GHz. The Ebeestock RF adapter provides excellent VSWR of 1.08:1 maximum and passive intermodulation of -166 dBc maximum.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		6	GHz
VSWR			1.08:1	
Insertion Loss			0.13	dB
Passive Intermodulation			-166	dBc
Operating Voltage (AC)			1,000	Vrms
Dielectric Withstanding Voltage (AC)			2,500	Vrms
Insulation Resistance	5,000			MOhms

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Low PIM 4.3-10 Male to 4.3-10 Male Adapter ET12030



Low PIM 4.3-10 Male to 4.3-10 Male Adapter



RF Adapters Technical Data Sheet

ET12030

Mechanical Specifications

Size

 Length
 1.34 in [34.04 mm]

 Width
 0.86 in [21.84 mm]

 Weight
 0.117 lbs [53.07 g]

Connector 1	Connector 2
4.3-10 Male	4.3-10 Male
Standard	Standard
100	100
22 mm	22 mm
6 lbs [2.72 Kg]	6 lbs [2.72 Kg]
	4.3-10 Male Standard 100 22 mm

Material Specifications

	Connector 1		Connector 2		
Description	Material	Plating	Material	Plating	
Туре	4.3-10 Male		4.3-10 Male		
Contact	Bronze	Silver	Bronze	Silver	
Insulation	PTFE		PTFE		
Body	Brass	Tri-Metal	Brass	Tri-Metal	
Gasket	Silicone				
Coupling Nut	Brass	Tri-Metal	Brass	Tri-Metal	

Environmental Specifications

Temperature

Operating Range -55 to +90 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Low PIM 4.3-10 Male to 4.3-10 Male Adapter ET12030



Low PIM 4.3-10 Male to 4.3-10 Male Adapter



RF Adapters Technical Data Sheet

ET12030

Low PIM 4.3-10 Male to 4.3-10 Male Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Low PIM 4.3-10 Male to 4.3-10 Male Adapter ET12030

URL: https://www.ebeestock.com/low-pim-4-3-10-male-to-4-3-10-male-adapter-0012030

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

ET12030 CAD Drawing Low PIM 4.3-10 Male to 4.3-10 Male Adapter

