


Bulkhead Mount 10-32 Female to BNC Female Adapter



RF Adapters Technical Data Sheet

ET1212

2

Configuration

- 10-32 Female Connector 1
- BNC Female Connector 2
- 50 Ohms

- Straight Body Geometry
- Bulkhead Mount Method

Features

- 10-32 Interface compliant with MIL-C-39012
- BNC Interface compliant with MIL-STD-348
- Gold Plated Contact
- Contact Plating per MIL-G-45204

Applications

Allows Connection Between Series
 General Purpose Test

Rack Mounted Equipment

Description

Ebeestock's ET12122 bulkhead 10-32 female to BNC female adapter is part of our full line of RF components available for same-day shipping. Our 10-32 to BNC adapter has a female to female gender configuration. This RF 10-32 bulkhead to BNC adapter allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Mechanical Specifications

Size			
Length	1.165 in [29	.59 mm]	
Width	0.688 in [17	'.48 mm]	
Weight	0.041 lbs [18.6 g]		
Type	10-32 Female	BNC Female	
Polarity	Standard	Standard	
Interface Specification	MIL-C-39012	MIL-STD-348	

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Bulkhead 10-32 Female to BNC Female Adapter ET12122



Bulkhead Mount 10-32 Female to BNC Female Adapter



RF Adapters Technical Data Sheet ET12122

Material Specifications

	Connector 1		Connector 2	
Description	Material	Plating	Material	Plating
Туре	10-32 Female	BNC Female		
Contact		Gold		Gold
		MIL-G-45204		MIL-G-45204
Insulation	PTFE		PTFE	
Outer Conductor	Brass	Nickel	Brass	Nickel
		QQ-N-290		QQ-N-290

Environmental Specifications

Temperature

Operating Range

-65 to +165 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Bulkhead 10-32 Female to BNC Female Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Bulkhead 10-32 Female to BNC Female Adapter ET12122

URL: https://www.ebeestock.com/bulkhead-mount-10-32-female-to-bnc-female-adapter-0012122

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

ET12122 CAD Drawing
Bulkhead 10-32 Female to BNC Female Adapter

