

Slide-On BMA Plug to SMA Female Adapter



RF Adapters Technical Data Sheet

ET12128

Configuration

- Slide-On BMA Plug Connector 1
- SMA Female Connector 2

- 50 Ohm
- Straight Body Geometry

Features

- Max VSWR of 1.15:1 up to 18 GHz
- Gold Plated Beryllium Copper Contact

Low-Engagement Force

Applications

- Allows Connection Between Series
- General Purpose Test
- Blind Mating

- Rack and Panel
- Phased Array Systems
- Base Stations

- RF Backplanes
- Test I/O

Description

Ebeestock's ET12128 slide-on BMA plug to SMA female adapter is part of our full line of RF components available for sameday shipping. Our BMA to SMA adapter has a plug to female gender configuration built of durable stainless steel. ET12128 BMA plug to SMA female adapter operates to 18 GHz. The Ebeestock RF adapter provides excellent VSWR of 1.15:1 maximum.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		18	GHz
VSWR			1.15:1	
Operating Voltage (AC)			350	Vrms
Dielectric Withstanding Voltage (AC)			1,000	Vrms
Insulation Resistance	5,000			MOhms

Mechanical Specifications

Size

 Length
 0.535 in [13.59 mm]

 Width
 0.3 in [7.62 mm]

 Weight
 0.009 lbs [4.08 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Slide-On BMA Plug to SMA Female Adapter ET12128



Slide-On BMA Plug to SMA Female Adapter



RF Adapters Technical Data Sheet

ET12128

Connector 1	Connector 2	
BMA Plug	SMA Female	
Standard	Standard	
6.07 lbs [2.75 Kg]		
	BMA Plug Standard	

Mechanical Specification Notes:

Recommended axial float mount for best electrical performance: 0.51 +/- 0.25 mm (.020" +/- .010)

Material Specifications

	Connector 1		Connec	tor 2	
Descriptio	n Material	Plating	Material	Plating	
Туре	Slide-On BMA Plug		SMA Female		
Contact	Beryllium Copper	Gold	Beryllium Copper	Gold	
Insulation	PTFE	PTFE			
Outer Conducto	r Passivated Stainless Steel		Passivated Stainless Steel		
Body	Passivated Stainless Steel		Passivated Stainless Steel		

Environmental Specifications

Temperature
Operating Range

-65 to +125 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Slide-On BMA Plug to SMA Female Adapter ET12128

www.ebeestock.com



Slide-On BMA Plug to SMA Female Adapter



RF Adapters Technical Data Sheet

ET12128

Slide-On BMA Plug to SMA Female Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Slide-On BMA Plug to SMA Female Adapter ET12128

URL: https://www.ebeestock.com/slide-on-bma-plug-to-sma-female-adapter-0012128

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

ET12128 CAD Drawing
Slide-On BMA Plug to SMA Female Adapter

