

Bulkhead Mount BNC Female to C Female Adapter



RF Adapters Technical Data Sheet

ET1215

5

Configuration

- BNC Female Connector 1
- C Female Connector 2
- 50 Ohms

- Straight Body Geometry
- Bulkhead Mount Method

Features

- BNC Interface compliant with MIL-STD-348
- C Interface compliant with MIL-STD-348
- Silver Plated Contact
- Contact Plating per QQ-S-365

Applications

Allows Connection Between Series
 General Purpose Test

Rack Mounted Equipment

Description

Ebeestock's ET12155 bulkhead BNC female to type C female adapter is part of our full line of RF components available for same-day shipping. Our BNC to type C adapter has a female to female gender configuration. This RF BNC bulkhead to type C adapter allows designers to create external connections on their product enclosures, and can be used in a variety of other rack mount and panel mount applications.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Mechanical Specifications

Size Length Width Weight	1.655 in [42.04 mm] 0.875 in [22.23 mm] 0.096 lbs [43.54 g]		
Type	BNC Female	C Female	
Polarity Interface Specification	Standard MIL-STD-348	Standard MIL-STD-348	

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Bulkhead BNC Female to C Female Adapter ET12155



Bulkhead Mount BNC Female to C Female Adapter



RF Adapters Technical Data Sheet ET12155

Material Specifications

	Connector 1		Connector 2		
Description	Material	Plating	Material	Plating	
Туре	BNC Female		C Female		
Contact		Silver		Silver	
		QQ-S-365		QQ-S-365	
Insulation	PTFE		PTFE		
Outer Conductor	Brass	Nickel	Brass	Nickel	
		QQ-N-290		QQ-N-290	

Environmental Specifications

Temperature

Operating Range

-65 to +165 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Bulkhead BNC Female to C Female Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Bulkhead BNC Female to C Female Adapter ET12155

URL: https://www.ebeestock.com/bulkhead-mount-bnc-female-to-c-female-adapter-0012155

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

www.ebeestock.com

ET12155 CAD Drawing
Bulkhead BNC Female to C Female Adapter

