



SECTION A-A

NOTES:

MATERIAL:

MAIN BODY AND DUST CAP: PBT + GF, UL94V-0

HOOD: MOLDED 25P PVC

ADAPTER:

BODY: COPPER, NICKEL PLATING

INSULATOR: WHITE PLASTIC STEEL

CONTACT: COPPER, GOLD PLATING

PHYSICAL CHARACTERISTICS:

OPERATING TEMPERATURE RANGE: -10 C TO +60 C.

STORAGE TEMPERATURE RANGE: -40 C TO +68 C.

HUMIDITY: 10% ~ 90% RH

IP RATING: IP68-WHEN DUST CAP IS ENGAGED.

ELECTRICAL:

IMPEDANCE: 75 OHM

PACKAGING:

ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

DUST CAP AND LANYARD NOT SHOWN



8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen, 523900, Dongguan, Guangdong, China.

Website: www.ebeestock.com

Email: sales@ebeestock.com

COAXIAL & FIBER OPTICS

UNLESS OTHERWISE SPECIFIED LEADING DIMENSIONS DIMENSIONS IN [] ARE
TOLERANCE
.X = ±.2 [5.08]
.XX = ±.02 [.51]
.XXX = ±.005 [.13]
CABLE LENGTH (L) TOLERANCE
L ≤ 12 [30]
12 [305] < L ≤ 60 [152]
60 [1524] < L ≤ 120 [304]
120 [3048] < L ≤ 300 [762]
300 [7620] < L
ALL DIMENSIONS ARE FOR REFERENCE

DWG TITLE	ET12176	DESIGN	waterproof-75-ohm-bnc-female-to-75-ohm-bnc-female-bulkhead-mount-adapter-ip68-in-series-0012176
SIZE A FSCM NO. 53919 CAD FILE 073102 SCALE N/A		127	

- NOTES:**
- UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
 - ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.