

HN Male to BNC Female Adapter



RF Adapters Technical Data Sheet

ET1219

4

Configuration

- HN Male Connector 1
- BNC Female Connector 2

Features

- Max VSWR of 1.5:1 up to 4 GHz
- HN Interface compliant with MIL-STD-348A
- BNC Interface compliant with MIL-STD-348A

- 50 Ohms
- Straight Body Geometry
- Gold Plated Brass Contact
- 30 µ-in min Gold Contact Plating

Applications

Allows Connection Between Series
 General Purpose Test

Description

Ebeestock's ET12194 HN male to BNC female adapter is part of our full line of RF components available for same-day shipping. Our HN to BNC adapter has a male to female gender configuration. ET12194 HN male to BNC female adapter operates to 4 GHz. The Ebeestock RF adapter provides good VSWR of 1.5:1 maximum.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

ctrical Specifications			
Erequency Range	DC	4	GHz
VSWR		1.5:1	
Operating Voltage (AC)		500	Vrms
Dielectric Withstanding Voltage (AC)		1,500	Vrms

Mechanical Specifications

Size

 Length
 1.508 in [38.3 mm]

 Width
 0.866 in [22 mm]

 Weight
 0.103 lbs [46.72 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: HN Male to BNC Female Adapter ET12194



HN Male to BNC Female Adapter



RF Adapters Technical Data Sheet ET12194

Description	Connector 1	Connector 2
Туре	HN Male	BNC Female
Polarity	Standard	Standard
Interface Specification	MIL-STD-348A	MIL-STD-348A

Material Specifications

	Connector 1		Connector 2	
Description	Material	Plating	Material	Plating
Туре	HN Male		BNC Female	
Contact	Brass	Gold	Brass	Gold
		30 µ-in minimum		30 µ-in minimum
Insulation	PTFE		PTFE	
Outer Conductor			Brass	Nickel
				100 μ-in minimum
Body	Brass	Nickel		
		100 μ-in minimum		
Gasket	Silicone			
Coupling Nut	Brass	Nickel		
		100 μ-in minimum		

Environmental SpecificationsTemperature

Operating Range

-65 to +165 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: HN Male to BNC Female Adapter ET12194



HN Male to BNC Female Adapter



RF Adapters Technical Data Sheet ET12194

HN Male to BNC Female Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: HN Male to BNC Female Adapter ET12194

URL: https://www.ebeestock.com/hn-male-to-bnc-female-adapter-0012194

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

ET12194 CAD Drawing HN Male to BNC Female Adapter

