

75 Ohm N Male to 75 Ohm BNC Male Adapter



RF Adapters Technical Data Sheet

ET1222

9

Configuration

- N Male Connector 1
- BNC Male Connector 2

- 75 Ohms
- Straight Body Geometry

Features

Typical VSWR of 1.4:1 up to 1,000 MHz

Gold Plated Brass Contact

Applications


• Allows Connection Between Series

General Purpose Test

Description

Ebeestock's ET12229 75 ohm type N male to BNC male adapter is part of our full line of RF components available for sameday shipping. Our type N to BNC adapter has a male to male gender configuration. ET12229 type N male to BNC male adapter operates to 1,000 MHz.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 75 Ohm N Male to BNC Male Adapter ET12229

www.ebeestock.com

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



75 Ohm N Male to 75 Ohm BNC Male Adapter



RF Adapters Technical Data Sheet ET12229

Material Specifications

| Description | Connector 1 | | Connector 2 | |
|--------------|-------------|---------|-------------|---------|
| | Material | Plating | Material | Plating |
| Туре | N Male | | BNC Male | |
| Contact | Brass | Gold | Brass | Gold |
| Insulation | PTFE | | PTFE | |
| Body | Brass | Nickel | Brass | Nickel |
| Coupling Nut | Brass | Nickel | Brass | Nickel |

Environmental Specifications

Temperature
Operating Range


-65 to +165 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Typical Performance Data



Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 75 Ohm N Male to BNC Male Adapter ET12229


8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



75 Ohm N Male to 75 Ohm BNC Male Adapter



RF Adapters Technical Data Sheet ET12229



75 Ohm N Male to BNC Male Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 75 Ohm N Male to BNC Male Adapter ET12229

URL: https://www.ebeestock.com/75-ohm-n-male-to-75-ohm-bnc-male-adapter-0012229

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. <a href="Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

ET12229 CAD Drawing 75 Ohm N Male to BNC Male Adapter

