

Precision N Male to BNC Female Adapter



RF Adapters Technical Data Sheet

ET1224

4

Configuration

- N Male Connector 1
- BNC Female Connector 2
- 50 Ohms

- Precision Design
- Straight Body Geometry

Features

- Max VSWR of 1.2:1 up to 8 GHz
- N Interface compliant with MIL-STD-348
- BNC Interface compliant with MIL-STD-348
- Gold Plated Beryllium Copper Contact

Applications

Allows Connection Between Series
 General Purpose Test

Precision Test & Measurement

Description

Ebeestock's ET12244 precision type N male to BNC female adapter is part of our full line of RF components available for same-day shipping. Our type N to BNC adapter has a male to female gender configuration in a precision design. ET12244 type N male to BNC female adapter operates to 8 GHz. The Ebeestock RF adapter provides excellent VSWR of 1.2:1 maximum.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications

Frequency Range	DC	8	GHz
VSWR		1.2:1	

Mechanical Specifications

Size

Length	1.85 in [46.	.99 mm]
Width	0.8 in [20.3	2 mm]
Weight	0.116 lbs [5	52.62 g]
Type	N Male	BNC Female
Polarity	Standard	Standard
Interface Specification	MIL-STD-348	MIL-STD-348

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price,

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



Precision N Male to BNC Female Adapter





Precision N Male to BNC Female Adapter



RF Adapters Technical Data Sheet ET12244

Material Specifications

Description	Connecto	r 1	Connector 2	
	on Material	Plating	Material	Plating
Туре	N Male		BNC Female	
Contact	Beryllium Copper	Gold	Beryllium Copper	Gold
Outer Conducto	or		Brass	Nickel
Body	Passivated Stainless Steel			
Coupling Nut	Brass	Nickel		

Environmental Specifications Temperature Operating Range

-65 to +125 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Precision N Male to BNC Female Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Precision N Male to BNC Female Adapter ET12244

URL: https://www.ebeestock.com/precision-n-male-to-bnc-female-adapter-0012244

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

ET12244 CAD Drawing Precision N Male to BNC Female Adapter

