

SMA Male to BNC Male Adapter



RF Adapters Technical Data Sheet

ET1224

6

Configuration

- SMA Male Connector 1
- BNC Male Connector 2

Features

- Max VSWR of 1.25:1 up to 8 GHz
- SMA Interface compliant with MIL-C-39012

- 50 Ohms
- Straight Body Geometry
- BNC Interface compliant with MIL-C-39012
- Gold Plated Beryllium Copper Contact

Applications


• Allows Connection Between Series

General Purpose Test

Description

Ebeestock's ET12246 SMA male to BNC male adapter is part of our full line of RF components available for same-day shipping. The SMA connector mates mechanically with commercially available 3.5mm and 2.92mm (K) connectors. Our SMA to BNC adapter has a male to male gender configuration. ET12246 SMA male to BNC male adapter operates to 8 GHz. The Ebeestock RF adapter provides excellent VSWR of 1.25:1 maximum.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.



Mechanical Specifications

Size

 Length
 1.52 in [38.61 mm]

 Width
 0.57 in [14.48 mm]

 Weight
 0.055 lbs [24.95 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male to BNC Male Adapter ET12246



SMA Male to BNC Male Adapter



RF Adapters Technical Data Sheet ET12246

Description	Connector 1	Connector 2
Туре	SMA Male	BNC Male
Polarity	Standard	Standard
Interface Specification	MIL-C-39012	MIL-C-39012
Hex Size	5/16 in.	

Material Specifications

	Connector 1		Connector 2	
Descriptio	n Material	Plating	Material	Plating
Туре	SMA Male		BNC Male	
Contact	Beryllium Copper	Gold	Beryllium Copper	Gold
Body	Passivated Stainless Steel		Brass	Nickel

Environmental Specifications

Temperature

Operating Range -65 to +125 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

SMA Male to BNC Male Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male to BNC Male Adapter ET12246

URL: https://www.ebeestock.com/sma-male-to-bnc-male-adapter-0012246

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

