



SECTION A-A

DUST CAP AND LANYARD NOT SHOW

NOTES:

MATERIAL:

MAIN BODY AND DUST CAP: PBT + GF, UL94V-0

HOOD: MOLDED 25P PVC

ADAPTER:

BODY: COPPER, NICKEL PLATING

INSULATOR: PLASTIC STEEL, BLUE

CONTACT: COPPER, BRIGHT NICKEL PLATING

PHYSICAL CHARACTERISTICS:

OPERATING TEMPERATURE RANGE: °-10 C TO°+60 C.

STORAGE TEMPERATURE RANGE: °-40 C TO°+68 C.

IP RATING: IP68-WHEN DUST CAP IS ENGAGED.

ELECTRICAL:

IMPEDANCE: 75 OHM

PACKAGING:

ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

THESE COMMODITIES, TECHNOLOGY OR SOFTWARE WERE EXPORTED FROM THE UNITED STATES IN ACCORDANCE WITH THE EXPORT ADMINISTRATION REGULATIONS. DIVERSION CONTRARY TO U.S. LAW PROHIBITED.

LEADING DIMENSION:
DIMENSIONS IN [] ARE

TOLERANCE

.X = ±.2 [5.08]

.XX = ±.02 [.51]

.XXX = ±.005 [.13]

CABLE LENGTH (L) TC

L ≤ 12 [30]

12 [305] < L ≤ 60 [152]

60 [1524] < L ≤ 120 [304]

120 [3048] < L ≤ 300 [762]

300 [7620] <

ALL DIMENSIONS ARE FOR REFERENCE



8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen, 523900, Dongguan, Guangdong, China.

Website: www.ebeestock.com

Email: sales@ebeestock.com

COAXIAL & FIBER OPTICS

DWG TITLE

ET12314

DES_

waterproof-75-ohm-f-female-to-75-ohm-f-female-bulkhead-mount-adapter-ip68-in-series-0012314

SIZE A | FSCM NO. 53919 | CAD FILE 073102 | SCALE N/A |

| 127

NOTES:

1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL.
2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME.