

75 Ohm N Male to 75 Ohm F Female Adapter



RF Adapters Technical Data Sheet

ET1232

6

Configuration

- N Male Connector 1
- F Female Connector 2

- 75 Ohms
- Straight Body Geometry

Features

Gold Plated Contact

• 30 µ-in min Gold Contact Plating

Applications

• Allows Connection Between Series

General Purpose Test

Description

Ebeestock's ET12326 75 ohm type N male to type F female adapter is part of our full line of RF components available for same-day shipping. ET12326 type N male to type F female adapter operates to 1,000 MHz.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

lectrical Specifications					
Frequency Range		1,000	MHz		
Operating Voltage (AC)		500	Vrms		

Mechanical Specifications

Size						
Length	1.346 in [34.19 mm]					
Width	0.827 in [21.01 mm]					
Weight	0.082 lbs [37.	19 g]				
Type	N Male	F Female				
Polarity	Standard	Standard				

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 75 Ohm N Male to F Female Adapter ET12326

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



75 Ohm N Male to 75 Ohm F Female Adapter



RF Adapters Technical Data Sheet ET12326

Material Specifications

Connector 1		Connector 2	
Material	Plating	Material	Plating
N Male		F Female	
Brass	Gold	Phosphor Bronze	Gold
	30 µ-in minimum		30 µ-in minimum
PTFE		PTFE	
		Brass	Nickel
			100 μ-in minimum
Brass	Nickel		
	100 μ-in minimum		
Brass	Nickel		
	100 μ-in minimum		
	Material N Male Brass PTFE Brass	Material Plating N Male Brass Gold 30 μ-in minimum PTFE Brass Nickel 100 μ-in minimum Brass Nickel	MaterialPlatingMaterialN MaleF FemaleBrassGoldPhosphor Bronze30 μ-in minimumPTFEPTFEPTFEBrassBrassNickel 100 μ-in minimumBrassNickel

Environmental SpecificationsTemperature

Operating Range

-40 to +60 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

75 Ohm N Male to F Female Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 75 Ohm N Male to F Female Adapter ET12326

URL: https://www.ebeestock.com/75-ohm-n-male-to-75-ohm-f-female-adapter-0012326

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

ET12326 CAD Drawing 75 Ohm N Male to F Female Adapter

