

HN Tee Adapter Male-Female-Male



RF Adapters Technical Data Sheet

ET1236

1

Configuration

- HN Male Connector 1
- HN Female Connector 2

- 50 Ohms
- Tee Body Geometry

Features

- HN interface compliant with MIL-STD-348
- Contact plating according to QQ-S-365

Applications

General Purpose Test

Silver Plated Contact

Description

Ebeestock's ET12361 HN tee adapter male-female-male is part of our full line of RF components available for same-day shipping. Our HN tee adapter has a male-female-male gender configuration. Tee adapters (also called tee connectors) are three port devices that can be used to split or combine a signal. Unlike power dividers/combiners, however, they do not provide matched impedance at all ports.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Mechanical Specifications

Size					
Length	2.55 in [64.77 mm]				
Width	0.88 in [22.35 mm]				
Height	1.49 in [37.85 mm]				
Weight	0.281 lbs [127.46 g]				
Type	HN Male	HN Female			
Polarity	Standard	Standard			
Interface Specification	MIL-STD-348	MIL-STD-348			

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: HN Tee Adapter Male-Female-Male ET12361



HN Tee Adapter Male-Female-Male



RF Adapters Technical Data Sheet ET12361

Material Specifications

	Connector 1		Connector 2	
Material	Plating	Material	Plating	
HN Male		HN Female		
	Silver		Silver	
	QQ-S-365		QQ-S-365	
PTFE		PTFE		
		Brass	Nickel	
			QQ-N-290	
Brass	Nickel			
	QQ-N-290			
Silicone Rubber		Silicone Rubber		
Brass	Nickel			
	QQ-N-290			
	HN Male PTFE Brass Silicone Rubber	HN Male Silver QQ-S-365 PTFE Brass Nickel QQ-N-290 Silicone Rubber Brass Nickel	HN Male Silver QQ-S-365 PTFE PTFE Brass Nickel QQ-N-290 Silicone Rubber Silicone Rubber Nickel	

Environmental Specifications

Temperature

Operating Range

-65 to +165 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

HN Tee Adapter Male-Female-Male from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: HN Tee Adapter Male-Female-Male ET12361

URL: https://www.ebeestock.com/hn-tee-adapter-male-female-male-0012361

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

ET12361 CAD Drawing HN Tee Adapter Male-Female-Male

