

75 Ohm N Female to 75 Ohm Mini SMB Jack Adapter



RF Adapters Technical Data Sheet

ET1241

7

Configuration

- N Female Connector 1
- Mini SMB Jack Connector 2

Features

- N Interface compliant with MIL-STD-348
- Mini SMB Interface compliant with MIL-STD-348
- 75 Ohms
- Straight Body Geometry
- Gold Plated Contact
- Contact Plating per MIL-G-45204

Applications

Allows Connection Between Series

General Purpose Test

Description

Ebeestock's ET12417 75 ohm type N female to Mini SMB jack adapter is part of our full line of RF components available for same-day shipping. Our type N to Mini SMB adapter has a female to jack gender configuration.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Mechanical Specifications

Size
Long

 Length
 1.38 in [35.05 mm]

 Width
 0.625 in [15.88 mm]

Weight 0.064 lbs [29.03 g]

Type N Female Mini SMB Jack
Polarity Standard Standard
Interface Specification MIL-STD-348 MIL-STD-348

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 75 Ohm N Female to Mini SMB Jack Adapter ET12417



75 Ohm N Female to 75 Ohm Mini SMB Jack Adapter



RF Adapters Technical Data Sheet ET12417

Material Specifications

Description	Connector 1		Connector 2	
	Material	Plating	Material	Plating
Туре	N Female		Mini SMB Jack	
Contact		Gold		Gold
		MIL-G-45204		MIL-G-45204
Insulation	PTFE		PTFE	
Outer Conductor	Brass	Nickel	Brass	Nickel
		QQ-N-290		QQ-N-290

Environmental Specifications

Temperature

Operating Range

-65 to +165 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

75 Ohm N Female to Mini SMB Jack Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: 75 Ohm N Female to Mini SMB Jack Adapter ET12417

URL: https://www.ebeestock.com/75-ohm-n-female-to-75-ohm-mini-smb-jack-adapter-0012417

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

ET12417 CAD Drawing
75 Ohm N Female to Mini SMB Jack Adapter

