

UHF Female to Mini UHF Male Adapter



RF Adapters Technical Data Sheet

ET12437

Configuration

- UHF Female Connector 1
- Mini UHF Male Connector 2

- 50 Ohm
- Straight Body Geometry

Features

• Max VSWR of 1.3:1 up to 300 MHz

Gold Plated Brass Contact

Applications

Allows Connection Between Series

General Purpose Test

Description

Ebeestock's ET12437 UHF female to Mini UHF male adapter is part of our full line of RF components available for same-day shipping. Our UHF to Mini UHF adapter has a female to male gender configuration. ET12437 UHF female to Mini UHF male adapter operates to 300 MHz. The Ebeestock RF adapter provides good VSWR of 1.3:1 maximum.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		300	MHz
VSWR			1.3:1	
Operating Voltage (AC)			335	Vrms

Mechanical Specifications

Size

 Length
 1.17 in [29.72 mm]

 Width
 0.65 in [16.51 mm]

 Weight
 0.041 lbs [18.6 g]

Connector 1	Connector 2	
UHF Female	Mini UHF Male	
Standard	Standard	
	UHF Female	UHF Female Mini UHF Male

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: UHF Female to Mini UHF Male Adapter ET12437



UHF Female to Mini UHF Male Adapter



RF Adapters Technical Data Sheet

ET12437

Material Specifications

	Connector 1		Conn	ector 2
Description	Material	Plating	Material	Plating
Туре	UHF Female		Mini UHF Male	
Contact	Brass	Gold	Brass	Gold
Insulation	PTFE		PTFE	
Outer Conductor	Brass	Nickel		
		100 μ-in minimum		
Body	Brass	Nickel	Brass	Nickel
		100μ in. minimum		100 μ-in minimum
Coupling Nut			Brass	Nickel
				100 μ-in minimum

Environmental Specifications

Temperature

Operating Range

-55 to +85 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:


UHF Female to Mini UHF Male Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.


Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: UHF Female to Mini UHF Male Adapter ET12437

URL: https://www.ebeestock.com/uhf-female-to-mini-uhf-male-adapter-0012437

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.







DWG TITLE ET12437	
NOTES: 1. UNLESS OTHERWISE SPECIFIED A 2. ALL SPECIFICATIONS ARE SUBJE 3. DIMENSIONS ARE IN INCHES [mm]	7 1 0 0 4 7
ALL DIMENSIONS IECT TO CHANGE I n].	
ARE NOMINAL. WITHOUT NOTICE	V П Л