

Slide-On MMBX Plug to MMBX Plug Snap-On Adapter, 4.8mm Long Bullet



RF Adapters Technical Data Sheet

ET12443

Configuration

- Slide-On MMBX Plug Connector 1
- Snap-On MMBX Plug Connector 2

- 50 Ohm
- Straight Body Geometry

Features

- Max VSWR of 1.08:1 up to 12.4 GHz
- Gold Plated Contact

- Reliable Snap-On connection method
- Mechanical misalignment tolerance of 4.5°/0.7mm Max

Applications

- General Purpose Test
- Low cost blind mate interconnect
- Multi circuit board radios
- Board to board applications requiring multiple coaxial connections

Description

Ebeestock's ET12443 slide-on MMBX plug to MMBX plug snap-on adapter is part of our full line of RF components available for same-day shipping. Our MMBX to MMBX adapter has a plug to plug gender configuration. ET12443 MMBX plug to MMBX plug adapter is gold plated and operates to 12.4 GHz. The Ebeestock RF adapter provides excellent VSWR of 1.08:1 maximum.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		12.4	GHz
VSWR			1.08:1	
Insertion Loss			0.42	dB
Operating Voltage (AC)			330	Vrms
Dielectric Withstanding Voltage (AC)			1,000	Vrms
Insulation Resistance	1,000			MOhms

Mechanical Specifications

Size

 Length
 0.189 in [4.8 mm]

 Width
 0.149 in [3.78 mm]

 Weight
 0.00022 lbs [0.1 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Slide-On MMBX Plug to MMBX Plug Snap-On Adapter, 4.8mm Long Bullet ET12443

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



Slide-On MMBX Plug to MMBX Plug Snap-On Adapter, 4.8mm Long Bullet



RF Adapters Technical Data Sheet

ET12443

Description	Connector 1	Connector 2
Type	MMBX Plug	MMBX Plug
Polarity	Standard	Standard
Mating Cycles	100	100
Contact Captivation Axial Force, Min	2.25 lbs [1.02 Kg]	2.25 lbs [1.02 Kg]

Material Specifications

	Connector 1		Connector 2		
Description	Material	Plating	Material	Plating	
Туре	Slide-On MMBX Plug		Snap-On MMBX Plug		
Contact	Beryllium Copper	Gold	Beryllium Copper	Gold	
Insulation	PTFE		PTFE		
Outer Conductor	Bronze	Gold	Bronze	Gold	
Body	Bronze	Gold	Bronze	Gold	

Environmental SpecificationsTemperature

Operating Range

-55 to +155 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Slide-On MMBX Plug to MMBX Plug Snap-On Adapter, 4.8mm Long Bullet ET12443



Slide-On MMBX Plug to MMBX Plug Snap-On Adapter, 4.8mm Long Bullet



RF Adapters Technical Data Sheet

ET12443

Slide-On MMBX Plug to MMBX Plug Snap-On Adapter, 4.8mm Long Bullet from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: Slide-On MMBX Plug to MMBX Plug Snap-On Adapter, 4.8mm Long Bullet ET12443

URL: https://www.ebeestock.com/slide-on-mmbx-plug-to-mmbx-plug-snap-on-adapter-4-8mm-long-bulle t-0012443

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

ET12443 CAD Drawing
Slide-On MMBX Plug to MMBX Plug Snap-On Adapter, 4.8mm Long Bullet

