

SMA Female to MMBX Plug Snap-On Adapter, With Male Center Contact



RF Adapters Technical Data Sheet

ET12448

Configuration

- SMA Female Connector 1
- Snap-On MMBX Plug Connector 2

Features

- Max VSWR of 1.08:1 up to 12.4 GHz
- 51µ in. minimum contact plating
- Gold Plated Beryllium Copper Contact

- 50 Ohms
- Straight Body Geometry
- Reliable Snap-On connection method
- Mechanical misalignment tolerance of 4.5°/0.7mm Max

Applications

- Allows Connection Between Series
- General Purpose Test
- Low cost blind mate interconnect
- Multi circuit board radios
- Board to board applications requiring multiple coaxial connections

Description

Ebeestock's ET12448 SMA female to MMBX plug snap-on adapter, is part of our full line of RF components available for same-day shipping. The SMA connector mates mechanically with commercially available 3.5mm and 2.92mm (K) connectors. Our SMA to MMBX adapter has a female to plug gender configuration. ET12448 SMA female to MMBX plug adapter is gold plated and operates to 12.4 GHz. The Ebeestock RF adapter provides excellent VSWR of 1.08:1 maximum.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		12.4	GHz
VSWR			1.08:1	
Insertion Loss			0.42	dB
Operating Voltage (AC)			330	Vrms
Dielectric Withstanding Voltage (AC)			500	Vrms
Insulation Resistance	1,000			MOhms

Mechanical Specifications

Size

 Length
 0.58 in [14.73 mm]

 Width
 0.25 in [6.35 mm]

 Weight
 0.011 lbs [4.99 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female to MMBX Plug Snap-On Adapter, with male center contact ET12448

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



SMA Female to MMBX Plug Snap-On Adapter, With Male Center Contact



RF Adapters Technical Data Sheet

ET12448

Description	Connector 1	Connector 2
Type	SMA Female	MMBX Plug
Polarity	Standard	Standard
Mating Cycles	500	500
Contact Captivation Axial Force, Min	2.25 lbs [1.02 Kg]	2.25 lbs [1.02 Kg]

Material Specifications

	Connector 1		Connector 2	
Description	Material	Plating	Material	Plating
Туре	SMA Female		Snap-On MMBX Plug	
Contact Bery	Beryllium Copper	Gold	Beryllium Copper	Gold
		51µ in. minimum		51µ in. minimum
Insulation	PTFE		PTFE	
Outer Conductor E	Beryllium Copper	Gold	Beryllium Copper	Gold
		8µ in. minimum		8µ in. minimum
Body	Beryllium Copper	Gold	Beryllium Copper	Gold
		8µ in. minimum		8µ in. minimum

Environmental Specifications

Temperature

Operating Range

-55 to +155 deg C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female to MMBX Plug Snap-On Adapter, with male center contact ET12448

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



SMA Female to MMBX Plug Snap-On Adapter, With Male Center Contact



RF Adapters Technical Data Sheet

ET12448

SMA Female to MMBX Plug Snap-On Adapter, with male center contact from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female to MMBX Plug Snap-On Adapter, with male center contact ET12448

URL: https://www.ebeestock.com/sma-female-to-mmbx-plug-snap-on-adapter-with-male-center-contact -0012448

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

ET12448 CAD Drawing
SMA Female to MMBX Plug Snap-On Adapter, with male center contact

