

SMA Female to MMCX Jack Adapter



RF Adapters Technical Data Sheet

ET1245

7

Configuration

- SMA Female Connector 1
- MMCX Jack Connector 2

Features

- SMA interface compliant with MIL-STD-348
- MMCX interface compliant with MIL-C-39012
- Contact plating according to MIL-G-45204
- SMA Interface compliant with MIL-STD-348

- 50 Ohm
- Straight Body Geometry
- MMCX Interface compliant with MIL-C-39012
- Gold Plated Contact
- Contact Plating per MIL-G-45204

Applications

- Allows Connection Between Series
- General Purpose Test
- Allows Connection Between Series
- General Purpose Test

Description

Ebeestock's ET12457 SMA female to MMCX jack adapter is part of our full line of RF components available for same-day shipping. The SMA connector mates mechanically with commercially available 3.5mm and 2.92mm (K) connectors. Our SMA to MMCX adapter has a female to jack gender configuration.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Mechanical Specifications

S	ıze	

 Length
 0.682 in [17.32 mm]

 Width
 0.25 in [6.35 mm]

 Weight
 0.0084 lbs [3.81 g]

Type	SMA Female	MMCX Jack	
Polarity	Standard	Standard	
Interface Specification	MIL-STD-348	MIL-C-39012	

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female to MMCX Jack Adapter ET12457



SMA Female to MMCX Jack Adapter



RF Adapters Technical Data Sheet ET12457

Material Specifications

	Connector 1		Connector 2	
Description	Material	Plating	Material	Plating
Туре	SMA Female		MMCX Jack	
Contact		Gold		Gold
		MIL-G-45204		MIL-G-45204
Insulation	PTFE		PTFE	
Outer Conductor	Brass	Nickel	Brass	Nickel
		QQ-N-290		QQ-N-290

Environmental SpecificationsTemperature

Operating Range

-65 to +165 °C

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

SMA Female to MMCX Jack Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Female to MMCX Jack Adapter ET12457

URL: https://www.ebeestock.com/sma-female-to-mmcx-jack-adapter-0012457

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

