

SMA Male to MMCX Jack Adapter



RF Adapters Technical Data Sheet

ET1245

8

Configuration

- SMA Male Connector 1
- MMCX Jack Connector 2

- 50 Ohms
- Straight Body Geometry

Features

- SMA Interface compliant with MIL-STD-348
- MMCX Interface compliant with MIL-C-39012
- Gold Plated Contact
- Contact Plating per MIL-G-45204

Applications

• Allows Connection Between Series

General Purpose Test

Description

Ebeestock's ET12458 SMA male to MMCX jack adapter is part of our full line of RF components available for same-day shipping. The SMA connector mates mechanically with commercially available 3.5mm and 2.92mm (K) connectors. Our SMA to MMCX adapter has a male to jack gender configuration.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

Mechanical Specifications

Size Length Width Weight	0.72 in [18.29 0.312 in [7.92 0.009 lbs [4.08	mm]
Type	SMA Male	MMCX Jack
Polarity	Standard	Standard
Interface Specification	MIL-STD-348	MIL-C-39012
Hex Size	5/16 in.	
Mating Torque	3 to 5 in-lbs [0.34 to 0.57 Nm]	

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male to MMCX Jack Adapter ET12458

www.ebeestock.com



SMA Male to MMCX Jack Adapter



RF Adapters Technical Data Sheet ET12458

Material Specifications

	Connector 1		Connector 2	
Description	Material	Plating	Material	Plating
Туре	SMA Male		MMCX Jack	
Contact		Gold		Gold
		MIL-G-45204		MIL-G-45204
Insulation	PTFE		PTFE	
Outer Conductor			Brass	Nickel
				QQ-N-290
Body	Brass	Nickel		
		QQ-N-290		
Coupling Nut	Brass	Nickel		
		QQ-N-290		

Compliance Certifications (see product page for current document)


SMA Male to MMCX Jack Adapter from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: SMA Male to MMCX Jack Adapter ET12458

URL: https://www.ebeestock.com/sma-male-to-mmcx-jack-adapter-0012458

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

ET12458 CAD Drawing SMA Male to MMCX Jack Adapter



E AT ANY TIME.	127
ري _:	SIZE A
NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTI 3. DIMENSIONS ARE IN INCHES [mm].	SCALE N/A
SPECIFIED / ARE SUBJE NCHES [mm]	092302
THERWISE SIFICATIONS	CAD FILE
NOTES: 1. UNLESS (2. ALL SPEC 3. DIMENSIC	53919
	FSCM NO.
DWG TITLE ET12458	REV