

N Female to N Female Adapter, With Body Flats



# RF Adapters Technical Data Sheet

ET12473

## Configuration

- N Female Connector 1
- N Female Connector 2

### Features

- Max VSWR of 1.2:1 up to 18 GHz
- 1.3 µm minimum contact plating

## Applications

General Purpose Test

- 50 Ohm
- Straight Body Geometry
- Gold Plated Beryllium Copper Contact

#### Description

Ebeestock's ET12473 type N female to type N female adapter is part of our full line of RF components available for same-day shipping. Our type N to type N adapter has a female to female gender configuration. ET12473 type N female to type N female adapter operates to 18 GHz. The Ebeestock RF adapter provides excellent VSWR of 1.2:1 maximum.

RF adapters are often used to enable connections between two connector types that would otherwise not mate. Certain adapter configurations can also be used to protect connectors on expensive equipment where the number of connect/disconnect cycles is high. An RF, microwave or millimeter wave adapter is connected to the equipment, and the commonly changed connection is made with the adapter which can be easily replaced when it wears out after high usage; such adapters are referred to as connector savers. Ebeestock also offers bulkhead, panel mount, hermetically sealed, reverse polarity, and isolated ground adapter varieties to serve all of your RF, microwave and millimeter wave needs.

### Electrical Specifications

Description	Minimum	Typical	Maximum	Units
Frequency Range	DC		18	GHz
VSWR			1.2:1	
Operating Voltage (AC)			1,000	Vrms
Dielectric Withstanding Voltage (AC)			2,500	Vrms

Electrical Specification Notes: Values at 25°C, sea level.

#### Mechanical Specifications

Size

Length Weight

1.65 in [41.91 mm] 0.1015 lbs [46.04 g]

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Female to N Female Adapter, With Body Flats ET12473

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.



N Female to N Female Adapter, With Body Flats



# RF Adapters Technical Data Sheet

ET12473

Description	Connector 1	Connector 2
Туре	N Female	N Female
Polarity	Standard	Standard

#### Material Specifications

	Connector 1		Connector 2		
Description	Material	Plating	Material	Plating	
Туре	N Female		N Female		
Contact	Beryllium Copper	Gold	Beryllium Copper	Gold	
		1.3 µm minimum		1.3 µm minimum	
Insulation	PTFE		PTFE		
Outer Conductor P	assivated Stainless Steel		Passivated Stainless Steel		

## **Environmental Specifications**

Temperature

Operating Range -45 to +120 °C

Compliance Certifications (see product page for current document)

#### Plotted and Other Data

Notes:

N Female to N Female Adapter, With Body Flats from Ebeestock Enterprises has same day shipment for domestic and International orders. Our RF, microwave and millimeter wave products maintain a 99.4% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: N Female to N Female Adapter, With Body Flats ET12473

**URL:** https://www.ebeestock.com/n-female-to-n-female-adapter-with-body-flats-0012473

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Ebeestock reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Ebeestock does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Ebeestock does not assume any liability arising out of the use of any part or documentation.

8th Floor, Building 1, Yongfu Science and Technology Center Industrial Park, Nanzha District 5, Humen,523900, Dongguan, Guangdong, China.

